

# Exhibit 6



US007363416B2

(12) **United States Patent**  
**Chu**

(10) **Patent No.:** **US 7,363,416 B2**

(45) **Date of Patent:** **\*Apr. 22, 2008**

(54) **COMPUTER SYSTEM UTILIZING  
MULTIPLE COMPUTER MODULES WITH  
PASSWORD PROTECTION**

(58) **Field of Classification Search** ..... 710/300-317,  
710/62-64, 72-73; 709/214-219, 226-227  
See application file for complete search history.

(56) **References Cited**

(75) Inventor: **William W. Y. Chu**, Los Altos, CA  
(US)

U.S. PATENT DOCUMENTS

3,996,585 A 12/1976 Hogan

(73) Assignee: **ACQIS Technology, Inc.**, Mountain  
View, CA (US)

(Continued)

FOREIGN PATENT DOCUMENTS

EP 722138 A1 7/1996

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 329 days.

(Continued)

OTHER PUBLICATIONS

This patent is subject to a terminal dis-  
claimer.

CETIA Brochure "CETIA Powerengine CVME 603e" pp. 1-6  
downloaded from the internet at: <http://www.cetia.com/ProductAd-dOns/wp-47-01.pdf> on Feb. 15, 2006.

(Continued)

(21) Appl. No.: **11/124,851**

(22) Filed: **May 4, 2005**

Primary Examiner—Raymond N Phan

(74) Attorney, Agent, or Firm—Townsend and Townsend  
and Crew LLP

(65) **Prior Publication Data**

US 2005/0204083 A1 Sep. 15, 2005

(57) **ABSTRACT**

**Related U.S. Application Data**

(63) Continuation of application No. 11/097,694, filed on  
Mar. 31, 2005, which is a continuation of application  
No. 10/772,214, filed on Feb. 3, 2004, now Pat. No.  
7,099,981, which is a continuation of application No.  
09/569,758, filed on May 12, 2000, now Pat. No.  
6,718,415.


(60) Provisional application No. 60/134,122, filed on May  
14, 1999.

(51) **Int. Cl.**  
**G06F 13/20** (2006.01)

(52) **U.S. Cl.** ..... **710/313; 710/301; 710/315;**  
709/227

A computer system for multi-processing purposes. The  
computer system has a console comprising a first coupling  
site and a second coupling site. Each coupling site comprises  
a connector. The console is an enclosure that is capable of  
housing each coupling site. The system also has a plurality  
of computer modules, where each of the computer modules  
is coupled to a connector. Each of the computer modules has  
a processing unit, a main memory coupled to the processing  
unit, a graphics controller coupled to the processing unit,  
and a mass storage device coupled to the processing unit.  
Each of the computer modules is substantially similar in  
design to each other to provide independent processing of  
each of the computer modules in the computer system.

**94 Claims, 18 Drawing Sheets**



## US 7,363,416 B2

Page 2

## U.S. PATENT DOCUMENTS

4,623,964	A	11/1986	Getz et al.	
4,700,362	A	10/1987	Todd et al.	
4,769,764	A	9/1988	Levanon	
4,872,091	A	10/1989	Maniwa et al.	
4,890,282	A	12/1989	Lambert et al.	
4,918,572	A	4/1990	Tarver et al.	
4,939,735	A	7/1990	Fredericks et al.	
5,056,141	A	10/1991	Dyke	
5,086,499	A	2/1992	Mutone	
5,251,097	A	10/1993	Simmons et al.	
5,278,509	A	1/1994	Haynes et al.	
5,278,730	A	1/1994	Kikinis	
5,293,497	A	3/1994	Free	
5,311,397	A	5/1994	Harshberger et al.	
5,317,477	A	5/1994	Gillett	
5,319,771	A	6/1994	Takeda	
5,331,509	A	7/1994	Kikinis	
5,355,391	A	10/1994	Horowitz et al.	
5,428,806	A	6/1995	Pocrass	
5,436,857	A	7/1995	Nelson et al.	
5,463,742	A	10/1995	Kobayashi	
5,539,616	A	7/1996	Kikinis	
5,550,710	A	8/1996	Rahamim et al.	
5,550,861	A	8/1996	Chan et al.	
5,578,940	A	11/1996	Dillon	
5,600,800	A	2/1997	Kikinis et al.	
5,603,044	A	2/1997	Annapareddy et al.	
5,606,717	A	2/1997	Farmwald et al.	
5,608,608	A	3/1997	Flint et al.	
5,630,057	A	5/1997	Hait	
5,638,521	A	6/1997	Buchala et al.	
5,640,302	A *	6/1997	Kikinis ..... 361/687	
5,659,773	A	8/1997	Huynh et al.	
5,663,661	A	9/1997	Dillon et al.	
5,673,174	A	9/1997	Hamirani	
5,680,126	A	10/1997	Kikinis	
5,689,654	A	11/1997	Kikinis	
5,721,837	A	2/1998	Kikinis	
5,721,842	A	2/1998	Beasley et al.	
5,745,733	A	4/1998	Robinson	
5,752,080	A	5/1998	Ryan	
5,764,924	A	6/1998	Hong	
5,774,704	A	6/1998	Williams	
5,795,228	A	8/1998	Trumbull	
5,809,538	A	9/1998	Pollmann	
5,815,681	A	9/1998	Kikinis	
5,819,050	A	10/1998	Boehling et al.	
5,826,048	A	10/1998	Dempsey et al.	
5,848,249	A	12/1998	Garbus	
5,859,669	A	1/1999	Prentice	
5,907,566	A	5/1999	Benson et al.	
5,941,965	A	8/1999	Moroz	
5,948,047	A	9/1999	Jenkins et al.	
5,960,213	A	9/1999	Wilson	
5,968,144	A	10/1999	Walker et al.	
5,971,804	A	10/1999	Gallagher et al.	
5,977,989	A	11/1999	Lee et al.	
5,978,919	A *	11/1999	Doi et al. .... 726/36	
5,982,363	A	11/1999	Naift	
5,991,163	A	11/1999	Marconi et al.	
5,991,844	A	11/1999	Khosrowpour	
5,999,952	A	12/1999	Jenkins et al.	
6,002,442	A	12/1999	Li et al.	
6,003,105	A	12/1999	Vicard et al.	
6,011,546	A	1/2000	Bertram	
6,016,252	A	1/2000	Pignolet et al.	
6,028,643	A	2/2000	Jordan et al.	
6,029,183	A	2/2000	Jenkins et al.	
6,038,621	A	3/2000	Gale et al.	
6,040,792	A	3/2000	Watson et al.	
6,052,513	A	4/2000	MacLaren	

6,069,615	A	5/2000	Abraham et al.
6,088,224	A	7/2000	Gallagher et al.
6,088,752	A	7/2000	Ahern
6,157,534	A	12/2000	Gallagher et al.
6,163,464	A	12/2000	Ishibashi et al.
6,175,490	B1	1/2001	Papa et al.
6,202,169	B1	3/2001	Razzaghe-Ashrafi et al.
6,208,522	B1	3/2001	Manweiler et al.
6,216,185	B1	4/2001	Chu
6,260,155	B1	7/2001	Dellacona
6,289,376	B1	9/2001	Taylor et al.
6,304,895	B1	10/2001	Schneider et al.
6,311,268	B1	10/2001	Chu
6,314,522	B1	11/2001	Chu et al.
6,317,329	B1	11/2001	Dowdy et al.
6,321,335	B1	11/2001	Chu
6,332,180	B1	12/2001	Kauffman et al.
6,345,330	B2	2/2002	Chu
6,366,951	B1	4/2002	Schmidt
6,378,009	B1	4/2002	Pinkston, II et al.
6,381,602	B1	4/2002	Shoroff et al.
6,393,561	B1	5/2002	Hagiwara et al.
6,401,124	B1	6/2002	Yang et al.
6,425,033	B1	7/2002	Conway et al.
6,452,789	B1	9/2002	Pallotti et al.
6,452,790	B1	9/2002	Chu et al.
6,453,344	B1	9/2002	Ellsworth
6,496,361	B2	12/2002	Kim et al.
6,549,966	B1	4/2003	Dickens et al.
6,564,274	B1	5/2003	Heath et al.
6,643,777	B1	11/2003	Chu
6,718,415	B1	4/2004	Chu
6,725,317	B1	4/2004	Bouchier et al.
7,099,981	B2	8/2006	Chu
7,146,446	B2	12/2006	Chu

## FOREIGN PATENT DOCUMENTS

JP	6-289953	10/1994
WO	WO 92/18924	10/1992
WO	WO 94/00097	1/1994
WO	WO 95/13640	5/1995

## OTHER PUBLICATIONS

MPL Brochure "1st Rugged All in One Industrial 486FDX-133 MHz PC" pp. 1-2, downloaded from the internet at: <http://www.mpl.ch/DOCs/ds48600.pdf> on Feb. 15, 2006.

MPL Brochure "IPM 486 Brochure/IPM5 User Manual" pp. 1-9 downloaded from the internet at <http://www.mpl.ch/DOCs/u48600xd.pdf> on Feb. 15, 2006.

Snyder, Joel "Better Management through consolidation" pp. 1-6 downloaded from the internet at <http://www.opus1.com/www/jms/nw-con-0818rev.html>.

Bernal, Carlos, product brochure entitled: "PowerSMP Series 4000", (Mar. 1998) <<<http://www.winnetmag.com/Windows/Article/ArticleID/3095/3095.html>, downloaded from web on Jun. 22, 2004, 2 pgs.

Cragle, Jonathan, "Density System 1100", May 1999) <<<http://www.winnetmag.com/Windows/Article/ArticleID/5199/5199.html>>>, downloaded from web on Jun. 21, 2004, 4 pgs.

Feldman, Jonathan, "Rack Steady: The Four Rack-Mounted Servers That Rocked Our Network", <<<http://www.networkcomputing.com/shared/printArticle.jhtml?article=/910/910r3side1.htm...>>> Jun. 23, 2004, 3 pgs.

Fetters, Dave, "Cubix High-Density Server Leads the Way With Standout Management Software", (Feb. 8, 1999) <<<http://www.nwc.com/shared/printArticle.jhtml?article=/1003/1003r3fult.html&pub=nwc>>>, downloaded from web on Jun. 23, 2004, 5 pgs.

Gardner, Michael and Null, Christopher, "A Server Condominium", <<<http://www.lantimes.com/testing/98jun/806a042a.html>>>, Jun. 23, 2004, 3 pgs.

## US 7,363,416 B2

Page 3

Harrison, Dave, "VME in the Military: The M1A2 Main Battle Tank Upgrade Relies on COTS VME" <http://www.dy4.com>>>, (Feb. 9, 1998), pp. 1-34.

Williams, Dennis, "Consolidated Servers", (Feb. 17, 1997) <<<http://www.lantimes.com/testing/97compare/pcconsol.html>>> downloaded from web on Jun. 23, 2004, 2 pgs.

Williams, Dennis, "Executive Summary: Consolidate Now", (Feb. 17, 1997) <<<http://www.lantimes.com/testing/97feb/702b064a.html>>> downloaded from web on Jun. 23, 2004, 2 pgs.

Williams, Dennis, Top "Scores for Useability and Openness", (Feb. 17, 1997) <<<http://www.lantimes.com/testing/97feb/702b064a.html>>> downloaded from web on Jun. 23, 2004, 2 pgs.

Williams, Dennis, "ChatCom Inc. Chatterbox", (Feb. 17, 1997) <<<http://www.lantimes.com/testing/97feb/702b066a.html>>> downloaded from web on Jun. 23, 2004, 3 pgs.

Williams, Dennis, "EVERSYS Corp. System 8000", (Feb. 17, 1997) <<<http://www.lantimes.com/testing/97feb/702b070b.html>>> downloaded from web on Jun. 22, 2004, 4 pgs.

Williams, Dennis, "Cubix Corp. ERS/FT II", (Feb. 17, 1997) <<<http://www.lantimes.com/testing/97feb/702b068b.html>>> downloaded from web on Jun. 23, 2004, 4 pgs.

Crystal Advertisement for "Rackmount Computers", (©2000-2004) <<<http://www.crystalpc.com/products/roservers.asp>>>, downloaded from web on Jun. 17, 2004, 8 pgs.

Crystal Advertisement for "QuickConnect® Cable Management", (©2000-2004) <<<http://www.crystalpc.com/products/quickconnect.asp>>> downloaded from web on Jun. 17, 2004, 4 pgs.

Cubix Product Brochure entitled, "Density System", (©2000) <<<http://64.173.211.7/support/techinfo/system/density/density10.htm>>> downloaded from web on Jun. 22, 2004, 3 pgs.

Cubix Product Brochure entitled, "Density System, Technical Specifications", (©2000) <<<http://64.173.211.7/support/techinfo/system/density/info/spec.htm>>> downloaded from web on Jun. 22, 2004, 2 pgs.

Cubix Product Manual entitled, "Density System", Chapter 1-Introduction, (©2000) <<<http://64.173.211.7/support/techinfo/manuals/density/Chap-1.htm>>> downloaded from web on Jun. 22, 2004, 5 pgs.

Cubix, "Click on the front panel that matches your system", (©2000) <<<http://64.173.211.7/support/techinfo/system/density/density.htm>>>, downloaded from web on Jun. 22, 2004, 1 pg.

Cubix Product Manual entitled, "Density System", Chapter 2-Installation, (©2000) <<<http://64.173.211.7/support/techinfo/manuals/density/Chap-2.htm>>> downloaded from web on Jun. 22, 2004, 9 pgs.

Cubix Product Manual entitled, "Density System", Chapter 3-Operation, (©2000) <<<http://64.173.211.7/support/techinfo/manuals/density/Chap-3.htm>>> downloaded from web on Jun. 22, 2004, 4 pgs.

Cubix Product Manual entitled, "Density System", Chapter 4-Maintenance and Repair, (©2000) <<<http://64.173.211.7/support/techinfo/manuals/density/Chap-4.htm>>> downloaded from web on Jun. 22, 2004, 5 pgs.

Cubix, "What Are Groups?", (©2000) <<<http://64.173.211.7/support/techinfo/system/density/info/groups.htm>>>, downloaded from web on Jun. 22, 2004, 3 pgs.

Cubix, "SP 5200XS Series Plug-in Computers", (©2000) <<<http://64.173.211.7/support/techinfo/bc/sp5200xs/intro.htm>>>, downloaded from web on Jun. 22, 2004, 2 pgs.

Cubix, "SP 5200XS Series Technical Specifications", (©2000) <<<http://64.173.211.7/support/techinfo/bc/sp5200xs/spec.htm>>>, downloaded from web on Jun. 22, 2004, 2 pgs.

Cubix, "SP 5200 Series" Chapter 1-Introduction, (©2000) <<<http://64.173.211.7/support/techinfo/manuals/sp5200/chap-1.htm>>>, downloaded from web on Jun. 22, 2004, 3 pgs.

Cubix, "SP 5200 Series" Chapter 2-Switches & Jumpers, (©2000) <<<http://64.173.211.7/support/techinfo/manuals/sp5200/chap-2.htm>>>, downloaded from web on Jun. 22, 2004, 3 pgs.

Cubix, "SP 5200 Series" Chapter 3-Installation, (©2000) <<<http://64.173.211.7/support/techinfo/manuals/sp5200/chap-3.htm>>>, downloaded from web on Jun. 22, 2004, 4 pgs.

Cubix, "SP 5200 Series" Chapter 4-Technical Reference, (©2000) <<<http://64.173.211.7/support/techinfo/manuals/sp5200/chap-4.htm>>>, downloaded from web on Jun. 22, 2004, 3 pgs.

Cubix, "DP 6200 'D' Series Plug-in Computers", <<<http://64.173.211.7/support/techinfo/bc/dp/6200d/intro.htm>>>, downloaded from web on Jun. 22, 2004, 3 pgs.

Cubix, "Installing DP or SP Series Boards" (©2000) <<<http://64.173.211.7/support/techinfo/bc/dp/6200d/intro.htm>>>, downloaded from web on Jun. 22, 2004, 2 pgs.

Cubix, "Powering On/Off or Resetting Plug-in Computers in an Density System", (©2000) <<<http://64.173.211.7/support/techinfo/system/density/info/power.htm>>>, downloaded from the web on Jun. 22, 2004, 2 pgs.

Cubix, "Multiplexing Video, Keyboard & Mouse with Multiple Density Systems", (©2000) <<<http://64.173.211.7/support/techinfo/system/density/info/vkm-mux.htm>>>, downloaded from web on Jun. 22, 2004, 2 pgs.

eBay Advertisement for "Total IT Group Network Engines", <<<http://cgi.ebay.com/we/eBayISAPI.dll?ViewItem&item=5706388046&sspageName=STRK%3AMDDBI%3AMEB3AIT&rd=1>>>, downloaded from web on Jun. 25, 2004, 1 pg.

"Features Chart", (Feb. 1, 1997) <<<http://www.lantimes.com/testing/97feb/702b072a.html>>>, downloaded from web on Jun. 23, 2004, 3 pgs.

Internet Telephone Roundup, "Industrial Computers", <<<http://www.tmcnet.com/articles/itmag/0499/0499roundup.htm>>>, downloaded from web on Jun. 23, 2004, 5 pgs.

Press Release: Hiawatha, Iowa, (Mar. 1, 1997) entitled "Crystal Group Products Offer Industrial PCs with Built-in Flexibility", <<<http://www.crystalpc.com/news/pressreleases/prodpr.asp>>>, downloaded from web May 14, 2004, 2 pgs.

Press Release: Kanata, Ontario, Canada, (Apr. 1998) entitled "Enhanced COTS SBC from DY 4 Systems features 166MHz Pentium™ Processor" <<<http://www.realtime-info.be/VPRI/layout/display/pr.asp?pr.asp?PRID=363>>>, 2pgs.

Product Brochure entitled "SVME/DM-192 Pentium® II Single Board Computer" (Jun. 1999) pp. 1-9.

Product Brochure entitled "System 8000", <<<http://www.bomara.com/Eversys/briefDefault.htm>>>, downloaded from web on Jun. 22, 2004, 4 pgs.

Product Brochure entitled: "ERS/FT II System", (©2000) <<<http://64.173.211.7/support/techinfo/system/ersft2/ersft2.htm>>>, downloaded from web on Jun. 22, 2004, 4 pgs.

Product Manual entitled: "ERS II and ERS/FT II", Chap. 3, System Components, <<<http://64.173.211.7/support/techinfo/manuals/ers2/ers2-c3.htm>>>, downloaded from web on Jun. 22, 2004, 21 pgs.


Product Manual entitled: "ERS II and ERS/FT II", Chap. 6, Component Installation, <<<http://64.173.211.7/support/techinfo/manuals/ers2/ers2-c6.htm>>>, downloaded from web on Jun. 22, 2004, 18 pgs.

Windows Magazine, "Cubix PowerSMP Series 4000", Nov. 1997, <<http://www.techweb.com/winmag/library/1997/1101/ntent008.htm>> downloaded from the web on Jun. 22, 2004, p. NT07.

MPL, "The First Rugged All-in-One Industrial 486FDX-133 MHz PC", IPM486/IPM5 User Manual, 1998, pp. 1-24.

Snyder, Joel "Better Management through consolidation" pp. 1-6 downloaded from the internet at <http://opus1.com/www/jms/nw-con-0818rev.html>, unknown dated.

\* cited by examiner






FIG. 2




FIG. 3




FIG. 4






Fig. 5




FIG. 6




FIG. 7


**Computing System**

FIG. 8




FIG. 9






FIG. 11


	Symbol	Signal	Data Rate	Description
1	PDO RTN			GND
2	PDO +	Synch. To PCK	10 x clock rate	Computer to Peripheral LVDS Data 0 +
3	PDO -			Computer to Peripheral LVDS Data 0 -
4	PD1 RTN			GND
5	PD1 +	Synch. To PCK	10 x clock rate	Computer to Peripheral LVDS Data 1 +
6	PD1 -			Computer to Peripheral LVDS Data 1 -
7	PD2 RTN			GND
8	PD2 +	Synch. To PCK	10 x clock rate	Computer to Peripheral LVDS Data 2 +
9	PD2 -			Computer to Peripheral LVDS Data 2 -
10	PD3 RTN			GND
11	PD3 +	Synch. To PCK	10 x clock rate	Computer to Peripheral LVDS Data 3 +
12	PD3 -			Computer to Peripheral LVDS Data 3 -
13	PCK RTN			GND
14	PCK +	-Clock	Clock rate	Computer to Peripheral LVDS Clock +
15	PCK -			Computer to Peripheral LVDS Clock -
16	PCN RTN			GND
17	PCN +	Synch. To PCK	10 x clock rate	Computer to Peripheral LVDS Control +
18	PCN -			Computer to Peripheral LVDS Control -
19	PDR0 RTN			GND
20	PDR0 +	Synch. To PCKR	10 x clock rate	Peripheral to Computer LVDS Data 0 +
21	PDR0 -			Peripheral to Computer LVDS Data 0 -
22	PDR1 RTN			GND
23	PDR1 +	Synch. To PCKR	10 x clock rate	Peripheral to Computer LVDS Data 1 +
24	PDR1 -			Peripheral to Computer LVDS Data 1 -
25	PDR2 RTN			GND
26	PDR2 +	Synch. To PCKR	10 x clock rate	Peripheral to Computer LVDS Data 2 +
27	PDR2 -			Peripheral to Computer LVDS Data 2 -
28	PDR3 RTN			GND
29	PDR3 +	Synch. To PCKR	10 x clock rate	Peripheral to Computer LVDS Data 3 +
30	PDR3 -			Peripheral to Computer LVDS Data 3 -
31	PCKR RTN			GND
32	PCKR +	Reverse Dir. Clock	Clock rate	Peripheral to Computer LVDS Clock +
33	PCKR -			Peripheral to Computer LVDS Clock -
34	PCNR RTN			GND
35	PCNR +	Synch. To PCKR	10 x Clock rate	Peripheral to Computer LVDS Control +
36	PCNR -			Peripheral to Computer LVDS Control -
37	RESET#		Asynchronous	Reset

FIG.12



**FIG. 13**

PCK	CK+	CK+	CK+	CK+	CK+	CK-	CK-	CK-	CK-	CK-	CK+	CK+	CK+	CK+	CK+	CK-	CK-	CK-	CK-	CK-
PD0	BS0	CM0#	A00	A01	A02	A03	A04	A05	A06	A07	BS0	BE0#	D00	D01	D02	D03	D04	D05	D06	D07
PD1	BS1	CM1#	A08	A09	A10	A11	A12	A13	A14	A15	BS1	BE1#	D08	D09	D10	D11	D12	D13	D14	D15
PD2	BS2	CM2#	A16	A17	A18	A19	A20	A21	A22	A23	BS2	BE2#	D16	D17	D18	D19	D20	D21	D22	D23
PD3	BS3	CM3#	A24	A25	A26	A27	A28	A29	A30	A31	BS3	BE3#	D24	D25	D26	D27	D28	D29	D30	D31
PCN	CND	CN1	CN2	CN3	CN4	CN5	CN6	CN7	CN8	CN9	CN0	CN1	CN2	CN3	CN4	CN5	CN6	CN7	CN8	CN9



**FIG. 14**




FIG. 15

Name	Type	Pins	Description
AD[31::0]	TS	32	Multiplexed Address/Data. AD is driven to a valid state when GNT# is asserted.
C/BE[3::0]#	TS	4	Multiplexed Command/Byte Enables. For a two-address transaction, 1st address phase carries the command, and the 2nd address phase carries the transaction type. C/BE is driven to a valid state when GNT# is asserted.
FRAME#	STS	1	Indicates beginning and duration of a PCI transaction. When the bus is idle, FRAME# is driven to High for 1 cycle. A pull-up resistor sustains STS signal.
IRDY#	STS	1	Initiator Ready. IRDY# is driven High for 1 cycle if bus is idle, and the state is sustained by a pull-up resistor.
TRDY#	STS	1	Target Ready. When bus is idle, TRDY# is driven High for 1 cycle if bus is idle. An external pull-up resistor sustains STS signal.
DEVSEL#	STS	1	Device Select. DEVSEL# is asserted by target to indicate it is ready to accept the transaction. HIC decodes address of a transaction to decide the need to assert DEVSEL#. As an initiator, HIC waits for 5 cycles to detect assertion of DEVSEL# by the target; otherwise HIC terminates with a master abort. DEVSEL# is driven High for 1 cycle when bus is idle, and the state is sustained by a pull-up resistor.
STOP#	STS	1	Target request to stop transaction. There are 3 cases: STOP#, TRDY# & DEVSEL# asserted: disconnect with data transfer Only STOP# & DEVSEL# asserted: request initiator to retry later Only STOP# asserted: target abort STOP# is driven High for 1 cycle when bus is idle, and the state is sustained by a pull-up resistor.
PAR	TS	1	Even parity for 36 bits of AD & C/BE#. PAR is sent one cycle after address or data is valid. In write transaction, initiator sends PAR one cycle after write data is valid. In read transaction, target sends PAR one cycle after read data is valid.
LOCK#	Input	1	Initiator request lock on target downstream. LOCK# is asserted 1 clock cycle after address phase by an initiator wanting to perform an atomic operation that take more than one transaction to complete. HIC passes the LOCK# request to the secondary PCI bus. HIC does not drive LOCK# or propagate LOCK# upstream.
IDSEL#	Input	1	Chip Select for Type 0 configuration access. During a Type 0 configuration transaction, the initiator asserts IDSEL# during the address phase to select HIC. HIC responds by asserting DEVSEL#.
PERR#	STS	1	Data Parity Error on all transactions except Special Cycle. PERR# is driven one clock cycle after PAR. PERR# is asserted by target during write transactions, and by initiator during read transactions.
SERR#	OD	1	System Error. HIC asserts SERR# under the following conditions: Address parity error, Secondary bus SERR# asserted, Posted write transaction: data parity error on target bus, Posted write transaction discarded, Master abort, Target abort Delayed read or write transaction discarded, and Delayed transaction master timeout.
REQ#	TS	1	Request for bus. If a target retry or disconnect is received in response to initiating a transaction, HIC deasserts REQ# for at least 2 cycles before asserting it again.
GNT#	Input	1	Bus is granted to HIC. HIC can initiate transaction if GNT# is asserted and the bus is idle. When HIC is not requesting bus and GNT# is asserted, HIC must drive AD, C/BE, and PAR to valid logic levels.
CLKRUN#	I/OD	1	Input indicating clock status. HIC can request the central clock resource to start, speed up or maintain the PCI clock. There are 3 clocking states: Clock running, Clock about to stop/slow down, and Clock stopped/slowed.
PCICK	Input	1	PCI Clock. All inputs are sampled on the rising edge of PCICK. Frequency

FIG. 16




FIG. 17




FIG. 18

US 7,363,416 B2

1

# COMPUTER SYSTEM UTILIZING MULTIPLE COMPUTER MODULES WITH PASSWORD PROTECTION

## CROSS REFERENCE TO RELATED APPLICATIONS

The present application claims priority as a continuation of U.S. nonprovisional patent application Ser. No. 11/097,694, filed Mar. 31, 2005, which is a continuation of U.S. nonprovisional patent application Ser. No. 10/772,214, filed Feb. 3, 2004 now U.S. Pat. No. 7,099,981, which is a continuation of U.S. nonprovisional patent application Ser. No. 09/569,758, filed May 12, 2000 (Now U.S. Pat. No. 6,718,415), which claimed priority to U.S. Provisional Application No. 60/134,122 filed May 14, 1999, commonly assigned, and hereby incorporated by reference.

## BACKGROUND OF THE INVENTION

The present invention relates to computing devices. More particularly, the present invention provides a system including a plurality of computer modules that can independently operate to provide backup capability, dual processing, and the like. Merely by way of example, the present invention is applied to a modular computing environment for desk top computers, but it will be recognized that the invention has a much wider range of applicability. It can be applied to a server as well as other portable or modular computing applications.

Many desktop or personal computers, which are commonly termed PCs, have been around and used for over ten years. The PCs often come with state-of-art microprocessors such as the Intel Pentium™ microprocessor chips. They also include a hard or fixed disk drive such as memory in the giga-bit range. Additionally, the PCs often include a random access memory integrated circuit device such as a dynamic random access memory device, which is commonly termed DRAM. The DRAM devices now provide up to millions of memory cells (i.e., mega-bit) on a single slice of silicon. PCs also include a high resolution display such as cathode ray tubes or CRTs. In most cases, the CRTs are at least 15 inches or 17 inches or 20 inches in diameter. High resolution flat panel displays are also used with PCs.

Many external or peripheral devices can be used with the PCs. Among others, these peripheral devices include mass storage devices such as a Zip™ Drive product sold by Iomega Corporation of Utah. Other storage devices include external hard drives, tape drives, and others. Additional devices include communication devices such as a modem, which can be used to link the PC to a wide area network of computers such as the Internet. Furthermore, the PC can include output devices such as a printer and other output means. Moreover, the PC can include special audio output devices such as speakers the like.

PCs also have easy to use keyboards, mouse input devices, and the like. The keyboard is generally configured similar to a typewriter format. The keyboard also has the length and width for easily inputting information by way of keys to the computer. The mouse also has a sufficient size and shape to easily move a cursor on the display from one location to another location.

Other types of computing devices include portable computing devices such as "laptop" computers and the like. Although somewhat successful, laptop computers have many limitations. These computing devices have poor display technology. In fact, these devices often have a smaller

2

flat panel display that has poor viewing characteristics. Additionally, these devices also have poor input devices such as smaller keyboards and the like. Furthermore, these devices have limited common platforms to transfer information to and from these devices and other devices such as PCs.

Up to now, there has been little common ground between these platforms including the PCs and laptops in terms of upgrading, ease-of-use, cost, performance, and the like. Many differences between these platforms, probably somewhat intentional, has benefited computer manufacturers at the cost of consumers. A drawback to having two separate computers is that the user must often purchase both the desktop and laptop to have "total" computing power, where the desktop serves as a "regular" computer and the laptop serves as a "portable" computer. Purchasing both computers is often costly and runs "thousands" of dollars. The user also wastes a significant amount of time transferring software and data between the two types of computers. For example, the user must often couple the portable computer to a local area network (i.e., LAN), to a serial port with a modem and then manually transfer over files and data between the desktop and the portable computer. Alternatively, the user often must use floppy disks to "zip" up files and programs that exceed the storage capacity of conventional floppy disks, and transfer the floppy disk data manually.

Another drawback with the current model of separate portable and desktop computer is that the user has to spend money to buy components and peripherals the are duplicated in at least one of these computers. For example, both the desktop and portable computers typically include hard disk drives, floppy drives, CD-ROMs, computer memory, host processors, graphics accelerators, and the like. Because program software and supporting programs generally must be installed upon both hard drives in order for the user to operate programs on the road and in the office, hard disk space is often wasted.

One approach to reduce some of these drawbacks has been the use of a docking station with a portable computer. Here, the user has the portable computer for "on the road" use and a docking station that houses the portable computer for office use.

Similar to separate desktop and portable computers, there is no commonality between two desktop computers. To date, most personal computers are constructed with a single motherboard that provides connection for CPU and other components in the computer. Dual CPU systems have been available through Intel's slot 1 architecture. For example, two Pentium II cartridges can be plugged into two "slot 1" card slots on a motherboard to form a Dual-processor system. The two CPU's share a common host bus that connects to the rest of the system, e.g. main memory, hard disk drive, graphics subsystem, and others. Dual CPU systems have the advantage of increased CPU performance for the whole system. Adding a CPU cartridge requires no change in operating systems and application software. However, dual CPU systems may suffer limited performance improvement if memory or disk drive bandwidth becomes the limiting factor. Also, dual CPU systems have to time-share the processing unit in running multiple applications. CPU performance improvement efficiency also depends on software coding structure. Dual CPU systems provide no hardware redundancy to help fault tolerance. In running multiple applications, memory and disk drive data throughput will become the limiting factor in improving performance with multi-processor systems.



US 7,363,416 B2

3

The present invention generally relates to computer interfaces. More specifically, the present invention relates to an interface channel that interfaces two computer interface buses that operate under protocols that are different from that used by the interface channel.

Interfaces coupling two independent computer buses are well known in the art. A block diagram of a computer system utilizing such a prior art interface is shown in FIG. 5. In FIG. 5, a primary peripheral component interconnect (PCI) bus 505 of a notebook PC 500 is coupled to a secondary PCI bus 555 in a docking system 550 (also referred to as docking station 550) through high pin count connectors 501 and 502, which are normally mating connectors. The high pin count connectors 501 and 502 contain a sufficiently large number of pins so as to carry PCI bus signals between the two PCI buses without any translation. The main purpose for interfacing the two independent PCI buses is to allow transactions to occur between a master on one PCI bus and a target on the other PCI bus. The interface between these two independent PCI buses additionally includes an optional PCI to PCI bridge 560, located in the docking station 550, to expand the add on capability in docking station 550. The bridge 560 creates a new bus number for devices behind the bridge 560 so that they are not on the same bus number as other devices in the system thus increasing the add on capability in the docking station 550.

An interface such as that shown in FIG. 5 provides an adequate interface between the primary and secondary PCI buses. However, the interface is limited in a number of ways. The interface transfers signals between the primary and secondary PCI buses using the protocols of a PCI bus. Consequently, the interface is subject to the limitations under which PCI buses operate. One such limitation is the fact that PCI buses are not cable friendly. The cable friendliness of the interface was not a major concern in the prior art. However, in the context of the computer system of the present invention, which is described in the present inventor's (William W.Y. Chu's) application for "Personal Computer Peripheral Console With Attached Computer Module" filed concurrently with the present application on Sep. 8, 1998 and incorporated herein by reference, a cable friendly interface is desired for interfacing an attached computer module (ACM) and a peripheral console of the present invention. Furthermore, as a result of operating by PCI protocols, the prior art interface includes a very large number of signal channels with a corresponding large number of conductive lines (and a similarly large number of pins in the connectors of the interface) that are commensurate in number with the number of signal lines in the PCI buses which it interfaces. One disadvantage of an interface having a relatively large number of conductive lines and pins is that it costs more than one that uses a fewer number of conductive lines and pins. Additionally, an interface having a large number of conductive lines is bulkier and more cumbersome to handle. Finally, a relatively large number of signal channels in the interface renders the option of using differential voltage signals less viable because a differential voltage signal method would require duplicating a large number of signal lines. It is desirable to use a low voltage differential signal (LVDS) channel in the computer system of the present invention because an LVDS channel is more cable friendly, faster, consumes less power, and generates less noise, including electromagnetic interferences (EMI), than a PCI channel. The term LVDS is herein used to generically refer to low voltage differential signals and is not intended to be limited to any particular type of LVDS technology.

4

Thus, what is needed are computer systems that can have multiple computer modules. Each computer module has dedicated memory and disk drive, and can operate independently.

#### BRIEF SUMMARY OF THE INVENTION

According to the present invention, a technique including a method and device for multi-module computing is provided. In an exemplary embodiment, the present invention provides a system including a plurality of computer modules that can independently operate to provide backup capability, dual processing, and the like.

In a specific embodiment, the present invention provides a computer system for multi-processing purposes. The computer system has a console comprising a first coupling site and a second coupling site, e.g., computer module bay. Each coupling site comprises a connector. The console is an enclosure that is capable of housing each coupling site. The system also has a plurality of computer modules, where each of the computer modules is coupled to one of the connectors. Each of the computer modules has a processing unit, a main memory coupled to the processing unit, a graphics controller coupled to the processing unit, and a mass storage device coupled to the processing unit. Each of the computer modules is substantially similar in design to each other to provide independent processing of each of the computer modules in the computer system.

In an alternative specific embodiment, the present invention provides a multi-processing computer system. The system has a console comprising a first coupling site and a second coupling site. Each coupling site comprises a connector. The console is an enclosure that is capable of housing each coupling site. The system also has a plurality of computer modules, where each of the computer modules is coupled to one of the connectors. Each of the computer modules has a processing unit, a main memory coupled to the processing unit, a graphics controller coupled to the processing unit, a mass storage device coupled to the processing unit, and a video output coupled to the processing unit. Each of the computer modules is substantially similar in design to each other to provide independent processing of each of the computer modules in the computer system. A video switch circuit is coupled to each of the computer modules through the video output. The video switch is configured to switch a video signal from any one of the computer modules to a display.

Numerous benefits are achieved using the present invention over previously existing techniques. In one embodiment, the invention provides improved processing and maintenance features. The invention can also provide increased CPU performance for the whole system. The invention also can be implemented without changes in operating system and application software. The present invention is also implemented using conventional technologies that can be provided in the present computer system in an easy and efficient manner.

In another embodiment, the invention provides at least two users to share the same modular desktop system. Each user operates on a different computer module. The other peripheral devices, i.e. CDROM, printer, DSL connection, etc. can be shared. This provides lower system cost, less desktop space and more efficiency. Depending upon the embodiment, one or more of these benefits can be available. These and other advantages or benefits are described throughout the present specification and are described more particularly below.



US 7,363,416 B2

5

In still further embodiments, the present invention provides methods of using multiple computer modules.

The present invention encompasses an apparatus for bridging a first computer interface bus and a second computer interface bus, where each of the first and second computer interface buses have a number of parallel multiplexed address/data bus lines and operate at a clock speed in a predetermined clock speed range having a minimum clock speed and a maximum clock speed. The apparatus comprises an interface channel having a clock line and a plurality of bit lines for transmitting bits; a first interface controller coupled to the first computer interface bus and to the interface channel to encode first control signals from the first computer interface bus into first control bits to be transmitted on the interface channel and to decode second control bits received from the interface channel into second control signals to be transmitted to the first computer interface bus; and a second interface controller coupled to the interface channel and the second computer interface bus to decode the first control bits from the interface channel into third control signals to be transmitted on the second computer interface bus and to encode fourth control signals from the second computer interface bus into the second control bits to be transmitted on the interface channel.

In one embodiment, the first and second interface controllers comprise a host interface controller (HIC) and a peripheral interface controller (PIC), respectively, the first and second computer interface buses comprise a primary PCI and a secondary PCI bus, respectively, and the interface channel comprises an LVDS channel.

The present invention overcomes the aforementioned disadvantages of the prior art by interfacing two PCI or PCI-like buses using a non-PCI or non-PCI-like channel. In the present invention, PCI control signals are encoded into control bits and the control bits, rather than the control signals that they represent, are transmitted on the interface channel. At the receiving end, the control bits representing control signals are decoded back into PCI control signals prior to being transmitted to the intended PCI bus.

The fact that control bits rather than control signals are transmitted on the interface channel allows using a smaller number of signal channels and a correspondingly small number of conductive lines in the interface channel than would otherwise be possible. This is because the control bits can be more easily multiplexed at one end of the interface channel and recovered at the other end than control signals. This relatively small number of signal channels used in the interface channel allows using LVDS channels for the interface. As mentioned above, an LVDS channel is more cable friendly, faster, consumes less power, and generates less noise than a PCI bus channel, which is used in the prior art to interface two PCI buses. Therefore, the present invention advantageously uses an LVDS channel for the hereto unused purpose of interfacing PCI or PCI-like buses. The relatively smaller number of signal channels in the interface also allows using connectors having smaller pins counts. As mentioned above an interface having a smaller number of signal channels and, therefore, a smaller number of conductive lines is less bulky and less expensive than one having a larger number of signal channels. Similarly, connectors having a smaller number of pins are also less expensive and less bulky than connectors having a larger number of pins.

In one embodiment, the present invention encompasses an apparatus for bridging a first computer interface bus and a second computer interface bus, in a microprocessor based computer system where each of the first and second computer interface buses have a number of parallel multiplexed

6

address/data bus lines and operate at a clock speed in a predetermined clock speed range having a minimum clock speed and a maximum clock speed. The apparatus comprises an interface channel having a clock channel and a plurality of bit channels for transmitting bits; a first interface controller coupled to the first computer interface bus and to the interface channel to encode first control signals from the first computer interface bus into first control bits to be transmitted on the interface channel and to decode second control bits received from the interface channel into second control signals to be transmitted to the first computer interface bus; and a second interface controller coupled to the interface channel and the second computer interface bus to decode the first control bits from the interface channel into third control signals to be transmitted on the second computer interface bus and to encode fourth control signals from the second computer interface bus into the second control bits to be transmitted on the interface channel.

In one embodiment, the first and second interface controllers comprise a host interface controller (HIC) and a peripheral interface controller (PIC), respectively, the first and second computer interface buses comprise a primary PCI and a secondary PCI bus, respectively, and the interface channel comprises an LVDS channel.

In a preferred embodiment, the interface channel has a plurality of serial bit channels numbering fewer than the number of parallel bus lines in each of the PCI buses and operates at a clock speed higher than the clock speed at which any of the bus lines operates. More specifically, the interface channel includes two sets of unidirectional serial bit channels which transmit data in opposite directions such that one set of bit channels transmits serial bits from the HIC to the PIC while the other set transmits serial bits from the PIC to the HIC. For each cycle of the PCI clock, each bit channel of the interface channel transmits a packet of serial bits.

The HIC and PIC each include a bus controller to interface with the first and second computer interface buses, respectively, and to manage transactions that occur therein. The HIC and PIC also include a translator coupled to the bus controller to encode control signals from the first and second computer interface buses, respectively, into control bits and to decode control bits from the interface channel into control signals. Additionally, the HIC and PIC each include a transmitter and a receiver coupled to the translator. The transmitter converts parallel bits into serial bits and transmits the serial bits to the interface channel. The receiver receives serial bits from the interface channel and converts them into parallel bits.

According to the present invention, a technique including a method and device for securing a computer module using a password in a computer system is provided. In an exemplary embodiment, the present invention provides a security system for an attached computer module "ACM"). In an embodiment, the ACM inserts into a Computer Module Bay (CMB) within a peripheral console to form a functional computer.

In a specific embodiment, the present invention provides a computer module. The computer module has an enclosure that is insertable into a console. The module also has a central processing unit (i.e., integrated circuit chip) in the enclosure. The module has a hard disk drive in the enclosure, where the hard disk drive is coupled to the central processing unit. The module further has a programmable memory device in the enclosure, where the programmable memory device can be configurable to store a password for preventing a possibility of unauthorized use of the hard disk drive

US 7,363,416 B2

7

and/or other module elements. The stored password can be any suitable key strokes that a user can change from time to time. In a further embodiment, the present invention provides a permanent password or user identification code stored in flash memory, which also can be in the processing unit, or other integrated circuit element. The permanent password or user identification code is designed to provide a permanent "finger print" on the attached computer module.

In a specific embodiment, the present invention provides a variety of methods. In one embodiment, the present invention provides a method for operating a computer system such as a modular computer system and others. The method includes inserting an attached computer module "ACM") into a bay of a modular computer system. The ACM has a microprocessor unit (e.g., microcontroller, microprocessor) coupled to a mass memory storage device (e.g., hard disk). The method also includes applying power to the computer system and the ACM to execute a security program, which is stored in the mass memory storage device. The method also includes prompting for a user password from a user on a display (e.g., flat panel, CRT). In a further embodiment, the present method includes a step of reading a permanent password or user identification code stored in flash memory, or other integrated circuit element. The permanent password or user identification code provides a permanent finger print on the attached computer module. The present invention includes a variety of these methods that can be implemented in computer codes, for example, as well as hardware.

Numerous benefits are achieved using the present invention over previously existing techniques. The present invention provides mechanical and electrical security systems to prevent theft or unauthorized use of the computer system in a specific embodiment. Additionally, the present invention substantially prevents accidental removal of the ACM from the console. In some embodiments, the present invention prevents illegal or unauthorized use during transit. The present invention is also implemented using conventional technologies that can be provided in the present computer system in an easy and efficient manner. Depending upon the embodiment, one or more of these benefits can be available. These and other advantages or benefits are described throughout the present specification and are described more particularly below.

These and other embodiments of the present invention, as well as its advantages and features, are described in more detail in conjunction with the text below and attached Figs.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a simplified diagram of a computer system according to an embodiment of the present invention;

FIG. 2 is a simplified block diagram of a computer system according to an alternative embodiment of the present invention;

FIG. 3 is a simplified block diagram of a computer system according to a further alternative embodiment of the present invention; and

FIG. 4 is a simplified flow diagram of a method according to an embodiment of the present invention.

FIG. 5 is a block diagram of a computer system using a prior art interface between a primary and a secondary PCI bus.

FIG. 6 is a block diagram of one embodiment of a computer system using the interface of the present invention.

8

FIG. 7 is a partial block diagram of a computer system using the interface of the present invention as a bridge between the north and south bridges of the computer system.

FIG. 8 is a partial block diagram of a computer system in which the north and south bridges are integrated with the host and peripheral interface controllers, respectively.

FIG. 9 is a block diagram of one embodiment of the host interface controller and the peripheral interface controller of the present invention.

FIG. 10 is a detailed block diagram of one embodiment of the host interface controller of the present invention.

FIG. 11 is a detailed block diagram of one embodiment of the PIC of the present invention.

FIG. 12 is a table showing the symbols, signals, data rate and description of signals in a first embodiment of the XPBus.

FIG. 13 is a table showing the information transmitted on the XPBus during two clock cycles of the XPBus in one embodiment of the present invention where 10 data bits transmitted in each clock cycle of the XPBus.

FIG. 14 is a table showing information transmitted on the XPBus during four clock cycles of the XPBus in another embodiment of the present invention where 10 data bits are transmitted in each clock cycle of the XPBus.

FIG. 15 is a schematic diagram of the signal lines PCK, PD0 to PD3, and PCN.

FIG. 16 is a table showing the names, types, number of pins dedicated to, and the description of the primary bus PCI signals.

FIG. 17 is a simplified layout diagram of a security system for a computer system according to an embodiment of the present invention.

FIG. 18 is a simplified block diagram of a security system for a computer module according to an embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE INVENTION

According to the present invention, a technique including a method and device for multi-module computing is provided. In an exemplary embodiment, the present invention provides a system including a plurality of computer modules that can independently operate to provide backup capability, dual processing, and the like.

FIG. 1 is a simplified diagram of a computer system 100 according to an embodiment of the present invention. This diagram is merely an illustration and should not limit the scope of the claims herein. One of ordinary skill in the art would recognize other variations, modifications, and alternatives. The computer system 100 includes an attached computer module (i.e., ACM) 113, a desktop console 101, among other elements. The computer system also has another ACM module 117. Each ACM module has a respective slot 121, 119, which mechanically houses and electrically couples each ACM to the computer console. Also shown is a display 111, which connects to the console. Additionally, keyboard 109 and mouse 115 are also shown. A second display 102, keyboard 105, and mouse 107 can be coupled to the console in some optional embodiments to allow more than one user to operate the computer system. The computer system is modular and has a variety of components that are removable. Some of these components (or modules) can be used in different computers, workstations, computerized television sets, and portable or laptop units.

US 7,363,416 B2

9

In the present embodiment, each ACM **113** includes computer components, as will be described below, including a central processing unit "CPU"), IDE controller, hard disk drive, computer memory, and the like. The computer module bay (i.e., CMB) **121** is an opening or slot in the desktop console. The CMB houses the ACM and provides communication to and from the ACM. The CMB also provides mechanical protection and support to the ACM. The CMB has a mechanical alignment mechanism for mating a portion of the ACM to the console. The CMB further has thermal heat dissipation sinks, electrical connection mechanisms, and the like. Some details of the ACM can be found in co-pending patent application Ser. Nos. 09/149,882 and 09/149,548 filed Sep. 8, 1998, commonly assigned, and hereby incorporated by reference for all purposes.

In a specific embodiment, the present multiple computer module system has a peripheral console that has two or more computer bays that can receive a removable computer module or ACM. Multiple computer module system can function as a personal computer with only one ACM and the peripheral console. The second and additional ACM can be added later to increase overall system performance and reliability. The ACM operates independently as self-contained computer, communicates with each other through a high-speed serial communication and share most peripheral devices within the peripheral console. Each ACM controls its independent graphics subsystem and drives separate video output signals. A practical implementation is a dual ACM system. In a dual ACM system, two monitors can be used to display the two ACMs' graphics outputs at the same time. For a single monitor, a RGB switch is used to switch between the video outputs of the two ACMs and can be controlled by a command from the user. Similarly, input devices (i.e. keyboard and mouse) are switched between the two computer systems with a command from the user. Command from the user can be in the form of either a dedicated key on the keyboard or a special icon on the screen that the mouse can click on.

In most embodiments, the ACM includes an enclosure such as the one described with the following components, which should not be limiting:

- 1) A CPU with cache memory;
- 2) Core logic device or means;
- 3) Main memory;
- 4) A single primary Hard Disk Drive "HDD") that has a security program;
- 5) Flash memory with system BIOS and programmable user password;
- 6) Operating System, application software, data files on primary HDD;
- 7) An interface device and connectors to peripheral console;
- 8) A software controllable mechanical lock, lock control means, and other accessories.

The ACM connects to a peripheral console with power supply, a display device, an input device, and other elements. Some details of these elements with the present system are described in more detail below. In a dual ACM system, the primary ACM can connect directly to the peripheral board in the peripheral console. The second ACM can connect either directly or indirectly to the peripheral board. For indirect connection, a receptacle board is added to allow a cable connection to the peripheral board. This is to facilitate the mechanical positioning of the second ACM inside the computer chassis. The receptacle board approach can even be

10

used for the primary ACM if a high bandwidth peripheral bus, e.g. PCI Bus, is not connected from the primary ACM to the peripheral board.

The shared peripheral console has a chassis and a motherboard that connects the following devices:

- 1) Input means, e.g. keyboard and mouse,
- 2) Display means, e.g. RGB monitor,
- 3) Add-on means, e.g. PCI add-on slots,
- 4) Two Computer Module Bays (CMB) with connectors to two ACMs,
- 5) A serial communication Hub controller that interfaces to serial communication controller of both ACMs,
- 6) Shared storage subsystem, e.g. Floppy drive, CDROM drive, DVD drive, or 2nd Hard Drive,
- 7) Communication device, e.g. modem,
- 8) Power supply, and others.

The computer bay is an opening in the peripheral console that receives an ACM. CMB provides mechanical protection to ACM, mechanical alignment for connector mating, mechanical locking system to prevent theft and accidental removal, and connectors at the end of the opening for connecting to ACM. The interface bus between ACM and the peripheral console has a video bus, peripheral connections, serial communication connection, control signals and power connection. Video bus includes video output of graphics devices, i.e. analog RGB and control signals for monitor. Power connection supplies the power for ACM.

An implementation of peripheral sharing is the use of Ethernet controllers to bridge the communication between the two ACMs. Some of the peripheral devices residing in the peripheral console are shown in the simplified diagram of FIG. 2. As shown, the diagram is merely an illustration which should not limit the scope of the claims herein. One of ordinary skill in the art would recognize many other variations, alternatives, and modifications. As shown, a primary ACM **203** is connected to PCI peripheral devices in the peripheral console through the PCI bus **225** that passes through the connection between primary ACM **203** and peripheral console **201**. As shown, ACM has a CPU module **207** coupled to the PCI bus through a North Bridge **211**.

The CPU module can use a suitable microprocessing unit, microcontroller, digital signal processor, and the like. In a specific embodiment, the CPU module uses, for example, a 400 MHz Pentium II microprocessor module from Intel Corporation and like microprocessors from AMD Corporation, Cyrix Corporation (now National Semiconductor Corporation), and others. In other aspects, the microprocessor can be one such as the Compaq Computer Corporation Alpha Chip, Apple Computer Corporation PowerPC G3 processor, and the like. Further, higher speed processors are contemplated in other embodiments as technology increases in the future.

In the CPU module, peripheral controller **213** is coupled to BIOS/flash memory **217**. Additionally, the peripheral controller is coupled to a clock control logic, a configuration signal, and a peripheral bus. The ACM has the hard drive module **215**. Among other elements, the ACM includes north bridge **215**, graphics subsystem **223** (e.g., graphics accelerator, graphics memory), an IDE controller, and other components. Adjacent to and in parallel alignment with the hard drive module **215** is the PCI bus. In a specific embodiment, North Bridge unit **211** often couples to a computer memory **209**, to the graphics subsystem, and to the peripheral controller via the PCI bus. Graphics subsystem typically couples to a graphics memory, and other elements. IDE controller generally supports and provides timing signals necessary for the IDE bus. In the present embodiment, the



## US 7,363,416 B2

11

IDE controller is embodied as part of a P114XE controller from Intel, for example. Other types of buses than IDE are contemplated, for example EIDE, SCSI, 1394, and the like in alternative embodiments of the present invention.

The hard drive module or mass storage unit **215** typically includes a computer operating system, application software program files, data files, and the like. In a specific embodiment, the computer operating system may be the Windows98 operating system from Microsoft Corporation of Redmond Wash. Other operating systems, such as WindowsNT, MacOS8, Unix, and the like are also contemplated in alternative embodiments of the present invention. Further, some typical application software programs can include Office98 by Microsoft Corporation, Corel Perfect Suite by Corel, and others. Hard disk module **215** includes a hard disk drive. The hard disk drive, however, can also be replaced by removable hard disk drives, read/write CD ROMs, flash memory, floppy disk drives, and the like. A small form factor, for example 2.5", is currently contemplated, however, other form factors, such as PC card, and the like are also contemplated. Mass storage unit **240** may also support other interfaces than IDE.

Among other features, the computer system includes an ACM with security protection.

The ACM also has a network controller, which can be an Ethernet controller **219**, which is coupled to the North Bridge through the PCI bus. The North Bridge is coupled to the CPU. The Ethernet controller can be a 10/100 Base, such as Intel's 82559 or the like. Other types of network connection devices can also be used. For example, the invention can use Gbit Ethernet 1394, and USB 2.0. The network controller couples to a hub **233** in the console, which includes shared peripheral system **201**.

Also shown is the second ACM **205**. The second ACM has the same or similar components as the first ACM. Here, like reference numerals have been used for easy cross-referencing, but is not intended to be limiting. In some embodiments, the secondary ACM is not connected to the PCI bus in the peripheral console directly. The secondary ACM **219** accesses peripheral devices controlled by the primary ACM through the Ethernet connection to the primary ACM, e.g. CD-ROM, or PCI modem. The implementation is not restricted to Ethernet serial communication and can use other high-speed serial communication such as USB 2.0, and 1394. The Ethernet hub is coupled to an external output port **235**, which connects to an external network.

The primary hard disk drive in each ACM can be accessed by the other ACM as sharable hard drive through the Ethernet connection. This allows the easy sharing of files between the two independent computer modules. The Ethernet Hub Controller provides the high-speed communication function between the two computer modules. Ethernet data bandwidth of 100 Mbit/sec allows fast data communication between the two computer modules. The secondary ACM access peripheral devices of the primary ACM through the network connection provided by Ethernet link. The operating system, e.g. Windows 98, provides the sharing of resources between the two ACMs. In some embodiments, critical data in one ACM can be backup into the other ACM.

The Ethernet hub also couples to PCI bus **239**, which connects to PCI devices **241**, **243**, e.g., modem, SCSI controller. A flash memory **242** can also be coupled to the PCI bus. The flash memory can store passwords and security information, such as those implementations described in U.S. Ser. No. 09/183,493, which is commonly owned, and hereby incorporated by reference. The hub **233** also couples

12

to an I/O control **237**, which connects to keyboard/mouse switch **245**, which couples to keyboard/mouse **247**. Optionally, the keyboard/mouse switch also couples to a second keyboard/house **259** via PS2 or USB signal line **251**. The keyboard/mouse switch has at least a first state and a second state, which allow operation of respectively multiple keyboards or a single keyboard. The switch also couples to each I/O controller **221** in each ACM via lines **253**, **255**. The I/O control **237** also couples to an RGB switch **257**, which allows video signals to pass to the first monitor **259**. Alternatively, the RGB switch couples to a second monitor **261**. The RGB switch includes analog video switches such as MAXIM's MAX4545.

The peripheral system **201** also has an independent power supply **231** for each ACM. Each power supply provides power to each ACM. As merely an example, the power supply is a MICRO ATX 150W made by ENLIGHT, but can be others. The power supply is connected or coupled to each ACM through a separate line, for example. The independent power supply allows for independent operation of each ACM in some embodiments.

The above embodiments are described generally in terms of hardware and software. It will be recognized, however, that the functionality of the hardware can be further combined or even separated. The functionality of the software can also be further combined or even separated. Hardware can be replaced, at times, with software. Software can be replaced, at times, with hardware. Accordingly, the present embodiments should not be construed as limiting the scope of the claims here. One of ordinary skill in the art would recognize other variations, modifications, and alternatives.

FIG. 3 is a simplified block diagram **300** of a computer system according to an alternative embodiment of the present invention. This diagram is merely an example which should not limit the scope of the claims herein. One of ordinary skill in the art would recognizes many other variations, modifications, and alternatives. Like reference numerals are used in this FIG. as the previous FIGS. for easy referencing, but are not intended to be limiting. As shown, each ACM includes common elements as the previous FIG. A primary ACM **203** is connected to PCI peripheral devices in the peripheral console through the PCI bus **225** that passes through the connection between primary ACM **203** and peripheral console **201**. As shown, ACM has a CPU module **207** coupled to the PCI bus through a North Bridge **211**.

The CPU module can use a suitable microprocessing unit, microcontroller, digital signal processor, and the like. In a specific embodiment, the CPU module uses, for example, a 400 MHz Pentium II microprocessor module from Intel Corporation and like microprocessors from AMD Corporation, Cyrix Corporation (now National Semiconductor Corporation), and others. In other aspects, the microprocessor can be one such as the Compaq Computer Corporation Alpha Chip, Apple Computer Corporation PowerPC G3 processor, and the like. Further, higher speed processors are contemplated in other embodiments as technology increases in the future.

In the CPU module, peripheral controller **213** is coupled to BIOS/flash memory **217**. Additionally, the peripheral controller is coupled to a clock control logic, a configuration signal, and a peripheral bus. The ACM has the hard drive module **215**. Among other elements, the ACM includes north bridge **215**, graphics subsystem **223** (e.g., graphics accelerator, graphics memory), an IDE controller, and other components. Adjacent to and in parallel alignment with the hard drive module **215** is the PCI bus. In a specific embodiment, North Bridge unit **211** often couples to a computer

US 7,363,416 B2

13

memory 209, to the graphics subsystem, and to the peripheral controller via the PCI bus. Graphics subsystem typically couples to a graphics memory, and other elements. IDE controller generally supports and provides timing signals necessary for the IDE bus. In the present embodiment, the IDE controller is embodied as part of a P114XE controller from Intel, for example. Other types of buses than IDE are contemplated, for example EIDE, SCSI, 1394, and the like in alternative embodiments of the present invention.

The hard drive module or mass storage unit 215 typically includes a computer operating system, application software program files, data files, and the like. In a specific embodiment, the computer operating system may be the Windows98 operating system from Microsoft Corporation of Redmond Wash. Other operating systems, such as WindowsNT, MacOS8, Unix, and the like are also contemplated in alternative embodiments of the present invention. Further, some typical application software programs can include Office98 by Microsoft Corporation, Corel Perfect Suite by Corel, and others. Hard disk module 215 includes a hard disk drive. The hard disk drive, however, can also be replaced by removable hard disk drives, read/write CD ROMs, flash memory, floppy disk drives, and the like. A small form factor, for example 2.5", is currently contemplated, however, other form factors, such as PC card, and the like are also contemplated. Mass storage unit 240 may also support other interfaces than IDE.

Among other features, the computer system includes an ACM with security protection.

The ACM also has a network controller, which can be coupled to a serial port 302, which is coupled to the PCI bus in the ACM. The serial port is coupled to the peripheral console through a serial controller 301 in the serial console. The serial controller is connected to PCI bus 239. The serial controller is also coupled to a serial hub controller 303, which is coupled to the PCI bus and a second ACM. In a specific embodiment, a receptacle board 310 is added to connect to the second ACM. The purpose of the receptacle board is to allow a cable connection 307 to the peripheral board 300. The cable connection is possible because the signals needed to connect to the peripheral board can be limited to video, I/O, serial communication, and power. The serial communication controller can be placed on the receptacle board and not in the ACM. As shown, the serial bus controller couples to the PCI bus. The receptacle board also couples to power, graphics subsystem, I/O controller, and other elements, which may be on a common bus. The overall operation of the present configuration is similar to the previous one except it operates in serial communication mode.

The Dual ACM system can support different usage models:

1. One user using both ACMs concurrently with 1 or 2 monitors, and a common keyboard/mouse.
2. Two users using the two separate ACMs at the same time with separate monitors and keyboard/mouse. The 2 users share peripherals, e.g., printer, CDROM, and others. The two users share external networking.

To support 1 monitor for both ACMs, a video switch in the peripheral console is used to switch between the video outputs of the two ACMs. The system can be set to support either 1 monitor or 2-monitor mode. The user presses a special key on the keyboard or a special icon on the screen to switch the screen display from one ACM to the other. This same action causes the keyboard and mouse connections to switch from one ACM to the other ACM.

14

A dual ACM system can save space, wiring, and cost for a 2-person PC setup, with the added benefit that both PC systems can be accessed from one user site for increased system performance if the other user is not using the system. Files can be copied between the primary drive of both system and provides protection against a single ACM failure. Software needs to be developed to manage the concurrent use of two PC subsystems, the automatic sharing of selected files between the two systems, and fault tolerance.

The design with more than two computer modules can be implemented with the use of multi-port, serial communication hub controller and multi-port I/O switches. In one embodiment, a peripheral console has four computer bays for four separate computer modules. The computer modules communicate through a four port Ethernet hub. The video, keyboard, and mouse switch will cycle through the connection from each computer module to the external monitor, keyboard, and mouse with a push button sequentially. This embodiment is useful for a server that performs different functions concurrently, e.g. email, application hosting, web hosting, firewall, etc.

The above embodiments are described generally in terms of hardware and software. It will be recognized, however, that the functionality of the hardware can be further combined or even separated. The functionality of the software can also be further combined or even separated. Hardware can be replaced, at times, with software. Software can be replaced, at times, with hardware. Accordingly, the present embodiments should not be construed as limiting the scope of the claims here. One of ordinary skill in the art would recognize other variations, modifications, and alternatives.

FIG. 4 is a simplified diagram of a method according to an embodiment of the present invention. This diagram is merely an example which should not limit the scope of the claims herein. One of ordinary skill in the art would recognize many other variations, modifications, and alternatives. The present diagram illustrates an automatic file backup procedure from one computer module to the other. As shown, a user selects (step 401) a certain file in one of the computer module for automatic backup. Next, the method determines if another module is available, step 403. If so, the method in the originating module requests the other computer module to create (step 405) backup file. Alternatively, the method alerts the user of the missing or malfunctioning module, step 429. The method then has the user try later 431, once the missing or malfunctioning module has been replaced or repaired. Next, the method determines if there is sufficient storage available in the other computer module for the backup files. If so, the method goes to the next step. (Alternatively, the method prompts (step 433) a message to the user indicating that the storage is full.) In the next step, the method stores the backup file in memory of the other module. After the backup file has been successfully created (step 409), the software in the originating ACM sets a timer to check (step 411) for file modification via branches 423, 427 through continue, step 425 process. If a file selected for backup has been modified (step 415), then the file is automatically back up to the other ACM again, step 417. Alternatively, the method returns to step 411 through branch 421.

The above embodiments are described generally in terms of hardware and software. It will be recognized, however, that the functionality of the hardware can be further combined or even separated. The functionality of the software can also be further combined or even separated. Hardware can be replaced, at times, with software. Software can be replaced, at times, with hardware. Accordingly, the present

## US 7,363,416 B2

15

embodiments should not be construed as limiting the scope of the claims here. One of ordinary skill in the art would recognize other variations, modifications, and alternatives.

FIG. 6 is a block diagram of one embodiment of a computer system 600 using the interface of the present invention. Computer system 600 includes an attached computer module (ACM) 605 and a peripheral console 610, which are described in greater detail in the application of William W. Y. Chu for "Personal Computer Peripheral Console With Attached Computer Module" filed concurrently with the present application on Sep. 8, 1998 and incorporated herein by reference. The ACM 605 and the peripheral console 610 are interfaced through an exchange interface system (XIS) bus 615. The XIS bus 615 includes power bus 616, video bus 617 and peripheral bus (XPBus) 618, which is also herein referred to as an interface channel. The power bus 616 transmits power between ACM 605 and peripheral console 610. In a preferred embodiment power bus 616 transmits power at voltage levels of 3.3 volts, 5 volts and 12 volts. Video bus 617 transmits video signals between the ACM 605 and the peripheral console 610. In a preferred embodiment, the video bus 617 transmits analog Red Green Blue (RGB) video signals for color monitors, digital video signals (such as Video Electronics Standards Association (VESA) Plug and Display's Transition Minimized Differential Signaling (TMDS) signals for flat panel displays), and television (TV) and/or super video (S-video) signals. The XPBus 618 is coupled to host interface controller (HIC) 619 and to peripheral interface controller (PIC) 620, which is also sometimes referred to as a bay interface controller.

In the embodiment shown in FIG. 6, HIC 619 is coupled to an integrated unit 621 that includes a CPU, a cache and a north bridge. In another embodiment, such as that shown in FIG. 7, the CPU 705 and north bridge 710 are separate rather than integrated units. In yet another embodiment, such as that shown in FIG. 8, the HIC and PIC are integrated with the north and south bridges, respectively, such that integrated HIC and north bridge unit 805 includes an HIC and a north bridge, while integrated PIC and south bridge unit 810 includes a PIC and a south bridge.

FIG. 9 is a more detailed block diagram of one embodiment of an HIC 905 and a PIC 955 of the present invention. HIC 905 includes a peripheral component interconnect (PCI) bus controller 910, an XPBus controller 915, a phase lock loop (PLL) clock 920 and an input/output (I/O) control 925. Similarly, PIC 955 includes a PCI bus controller 960, an XPBus controller 965, a PLL clock 970 and an I/O control 975. PCI bus controllers 910 and 960 are coupled to the primary and secondary PCI buses 930 and 980, respectively, and manage PCI transactions on the primary and secondary PCI buses 930 and 980, respectively. Similarly, XPBus Controllers 915 and 965 are coupled to XPBus 990. XPBus controller 915 drives the PCK line 991 and PD[0:3] and PCN lines 992 while XPBus controller 965 drives the PCKR lines 993, the PDR[0:3] and PCNR lines 994 and the RESET# line 995.

PCI bus controller 910 receives PCI clock signals from the primary PCI bus 930 and is synchronized to the PCI clock. However, as indicated in FIG. 9, the XPBus controller 915 is asynchronous with the PCI bus controller 910. Instead, the XPBus controller receives a clock signal from the PLL clock 920 and is synchronized therewith. PLL clock 920 generates a clock signal independent of the PCI clock. The asynchronous operation of the PCI bus and the XPBus allows the PCI Bus to change in frequency, for example as in a power down situation, without directly affecting the XPBus clocking. In the embodiment shown in FIG. 9, the

16

PLL clock 920 generates a clock signal having a frequency of 66 MHz, which is twice as large as the 33 MHz frequency of the PCI clock. (The clock signal generated by the PLL clock may have a clock speed different from, including lower than, 66 MHz. For example, in another embodiment, which is discussed in greater detail below, the PLL clock 920 generates a clock signal having a frequency of 132 MHz.)

The XPBus 990 operates at the clock speed generated by the PLL clock 920. Therefore, PCK, the clock signal from the XPBus controller 915 to XPBus controller 965 has the same frequency as the clock signal generated by PLL clock 920. XPBus controller 965 receives the PCK signal after it has been buffered and operates at the clock speed of PCK. The buffered version of the clock signal PCK is used to generate the clock signal PCKR, the clock signal from the XPBus controller 965 to XPBus controller 915. Accordingly, PCKR also has the same frequency as that generated by the PLL clock 920. The synchronous operation of PCK and PCKR provides for improved reliability in the system. In another embodiment, PCKR may be generated independently of PCK and may have a frequency different from that of PCK. It is to be noted that even when PCKR is generated from PCK, the slew between PCK and PCKR cannot be guaranteed because of the unknown cable length used for the XPBus. For a cable that is several feet long, the cable propagation delay alone can be several nano seconds.

As indicated in FIG. 9, PLL clock 970 is asynchronous with the XPBus controller 965. Instead, PLL clock 970 independently generates a clock signal that is used as a PCI clock signal on the secondary PCI bus 980. The secondary PCI bus 980 operates at the same clock speed as the primary PCI bus 930, namely at a frequency of 33 MHz.

FIG. 10 is a detailed block diagram of one embodiment of the HIC of the present invention. As shown in FIG. 10, HIC 1000 comprises bus controller 1010, translator 1020, transmitter 1030, receiver 1040, a PLL 1050, an address/data multiplexer (A/D MUX) 1060, a read/write controller (RD/WR Cntl) 1070, a video serial to parallel converter 1080 and a CPU control & general purpose input/output latch/driver (CPU CNTL & GPIO latch/driver) 1090.

HIC 1000 is coupled to an optional flash memory BIOS configuration unit 1001. Flash memory unit 1001 stores basic input output system (BIOS) and PCI configuration information and supplies the BIOS and PCI configuration information to A/D MUX 1060 and RD/WR Control 1070, which control the programming, read, and write of flash memory unit 1001.

Bus controller 1010 is coupled to the host PCI bus, which is also referred to herein as the primary PCI bus, and manages PCI bus transactions on the host PCI bus. Bus controller 1010 includes a slave (target) unit 1011 and a master unit 1016. Both slave unit 1011 and master unit 1016 each include two first in first out (FIFO) buffers, which are preferably asynchronous with respect to each other since the input and output of the two FIFOs in the master unit 1016 as well as the two FIFOs in the slave unit 1011 are clocked by different clocks, namely the PCI clock and the PCK. Additionally, slave unit 1011 includes encoder 1022 and decoder 1023, while master unit 1016 includes encoder 1027 and decoder 1028. The FIFOs 1012, 1013, 1017 and 1018 manage data transfers between the host PCI bus and the XPBus, which in the embodiment shown in FIG. 10 operate at 33 MHz and 106 MHz, respectively. PCI address/data (AD) from the host PCI bus is entered into FIFOs 1012 and 1017 before they are encoded by encoders 1022 and 1023. Encoders 1022 and 1023 format the PCI address/data bits to a form more suitable for parallel to serial conversion prior to



US 7,363,416 B2

17

transmittal on the XPBus. Similarly, address and data information from the receivers is decoded by decoders **1023** and **1028** to a form more suitable for transmission on the host PCI bus. Thereafter the decoded data and address information is passed through FIFOs **1013** and **1018** prior to being transferred to the host PCI bus. FIFOs **1012**, **1013**, **1017** and **1018**, allow bus controller **1010** to handle posted and delayed PCI transactions and to provide deep buffering to store PCI transactions.

Bus controller **1010** also comprises slave read/write control (RD/WR Cntl) **1014** and master read/write control (RD/WR Cntl) **1015**. RD/WR controls **1014** and **1015** are involved in the transfer of PCI control signals between bus controller **1010** and the host PCI bus.

Bus controller **1010** is coupled to translator **1020**. Translator **1020** comprises encoders **1022** and **1027**, decoders **1023** and **1028**, control decoder & separate data path unit **1024** and control encoder & merge data path unit **1025**. As discussed above encoders **1022** and **1027** are part of slave data unit **1011** and master data unit **1016**, respectively, receive PCI address and data information from FIFOs **1012** and **1017**, respectively, and encode the PCI address and data information into a form more suitable for parallel to serial conversion prior to transmittal on the XPBus. Similarly, decoders **1023** and **1028** are part of slave data unit **1011** and master data unit **1016**, respectively, and format address and data information from receiver **1040** into a form more suitable for transmission on the host PCI bus. Control encoder & merge data path unit **1025** receives PCI control signals from the slave RD/WR control **1014** and master RD/WR control **1015**. Additionally, control encoder & merge data path unit **1025** receives control signals from CPU CNTL & GPIO latch/driver **1090**, which is coupled to the CPU and north bridge (not shown in FIG. 10). Control encoder & merge data path unit **1025** encodes PCI control signals as well as CPU control signals and north bridge signals into control bits, merges these encoded control bits and transmits the merged control bits to transmitter **1030**, which then transmits the control bits on the data lines PD0 to PD3 and control line PCN of the XPBus. Examples of control signals include PCI control signals and CPU control signals. A specific example of a control signal is FRAME# used in PCI buses. A control bit, on the other hand is a data bit that represents a control signal. Control decoder & separate data path unit **1024** receives control bits from receiver **1040** which receives control bits on data lines PDR0 to PDR3 and control line PCNR of the XPBus. Control decoder & separate data path unit **1024** separates the control bits it receives from receiver **1040** into PCI control signals, CPU control signals and north bridge signals, and decodes the control bits into PCI control signals, CPU control signals, and north bridge signals all of which meet the relevant timing constraints.

Transmitter **1030** receives multiplexed parallel address/data (A/D) bits and control bits from translator **1020** on the AD[31:0] out and the CNTL out lines, respectively. Transmitter **1030** also receives a clock signal from PLL **1050**. PLL **1050** takes a reference input clock and generates PCK that drives the XPBus. PCK is asynchronous with the PCI clock signal and operates at 106 MHz, twice the speed of the PCI clock of 33 MHz. The higher speed is intended to accommodate at least some possible increases in the operating speed of future PCI buses. As a result of the higher speed, the XPBus may be used to interface two PCI or PCI-like buses operating at 106 MHz rather than 33 MHz or having 104 rather than 32 multiplexed address/data lines.

18

The multiplexed parallel A/D bits and some control bits input to transmitter **1030** are serialized by parallel to serial converters **1032** of transmitter **1030** into 10 bit packets. These bit packets are then output on data lines PD0 to PD3 of the XPBus. Other control bits are serialized by parallel to serial converter **1033** into 10 bit packets and send out on control line PCN of the XPBus.

A 10x multiplier **1031** receives PCK, multiplies it by a factor of 10 and feeds a clock signal 10 times greater than PCK into the parallel to serial converters **1032** and **1033**. The parallel to serial converters **1032** and **1033** perform bit shifting at 10 times the PCK rate to serialize the parallel bits into 10 bit packets. As the parallel to serial converters **1032** and **1033** shift bits at 10 times the PCK rate, the bit rate for the serial bits output by the parallel to serial converters is 10 times higher than PCK rate, i.e., 1060 MHz. However, the rate at which data packets are transmitted on the XPBus is the same as the PCK rate, i.e., 106 MHz. As the PCI buses operate at a clock and bit rate of 33 MHz, the XPBus has a clock rate that is twice as large and a bit rate per bit line (channel) that is 100 times as large as that of the PCI buses which it interfaces.

Receiver **1040** receives serial bit packets on data lines PDR0 to PDR3 and control line PCNR. Receiver **1040** also receives PCKR on the XPBus as well as the clock signal PCK from PLL **1050**. The synchronizer (SYNC) **1044** of receiver **1040** synchronizes the clock signal PCKR to the locally generated clock signal, PCK, in order to capture the bits received from the XPBus into PCK clock timing.

Serial to parallel converters **1042** convert the serial bit packets received on lines PDR0 to PDR3 into parallel address/data and control bits that are sent to decoders **1023** and **1028** and control decoder and separate data path unit **1024**, respectively. Serial to parallel converter **1043** receives control bit packets from control line PCNR, converts them to parallel control bits and sends the parallel control bits to control decoder & separate data path **1024**.

A 10x multiplier **1041** receives PCKR, multiplies it by a factor of 10 and feeds a clock signal 10 times greater than PCKR into the serial to parallel converters **1042** and **1043**. Because the bits on PDR0 to PDR3 and PCNR are transmitted at a bit rate of 10 times the PCKR rate, the serial to parallel converters **1042** and **1043** perform bit shifting at 10 times the PCKR rate to convert the 10 bit packets into parallel bits. It is to be noted that the rate at which bit packets are transmitted on the XPBus is the same as the PCKR rate, i.e., 106 MHz. The parallel data and control bits are thereafter sent to decoders **1023** and **1028** by way of the AD[3:0] in line and to control decoder & separate data path unit **1024** by way of CNTL in lines, respectively.

Reset control unit **1045** of HIC **1000** receives the signal RESET#, which is an independent system reset signal, on the reset line RESET#. Reset control unit **1045** then transmits the reset signal to the CPU CNTL & GPIO latch/driver unit **1090**.

As may be noted from the above, the 32 line host and secondary PCI buses are interfaced by 10 XPBus lines (PD0, PD1, PD2, PD3, PCN, PDR0, PDR1, PDR2, PDR3, PCNR). Therefore, the interface channel, XPBus, of the present invention uses fewer lines than are contained in either of the buses which it interfaces, namely the PCI buses. XPBus is able to interface such PCI buses without backup delays because the XPBus operates at a clock rate and a per line (channel) bit rate that are higher than those of the PCI buses.

In addition to receiving a reset signal, the CPU CNTL & GPIO latch/driver **1090** is responsible for latching input signals from the CPU and north bridge and sending the

US 7,363,416 B2

19

signals to the translator. It also takes decoded signals from the control decoder & separate data path unit **1024** and drives the appropriate signals for the CPU and north bridge.

In the embodiment shown in FIG. **10**, video serial to parallel converter **1080** is included in HIC **1000**. In another embodiment, video serial to parallel converter **1080** may be a separate unit from the HIC **1000**. Video serial to parallel converter **1080** receives serial video data on line VPD and a video clock signal VPCK from line VPCK of video bus **1081**. It then converts the serial video data into 16 bit parallel video port data and the appropriate video port control signals, which it transmits to the graphics controller (not shown in FIG. **10**) on the video port data [0:15] and video port control lines, respectively.

HIC **1000** handles the PCI bus control signals and control bits from the XPBus representing PCI control signals in the following ways:

1. HIC **1000** buffers clocked control signals from the host PCI bus, encodes them into control bits and sends the encoded control bits to the XPBus;
2. HIC **1000** manages the signal locally; and
3. HIC **1000** receives control bits from XPBus, translates the control bits into PCI control signals and sends the PCI control signals to the host PCI bus.

FIG. **11** is a detailed block diagram of one embodiment of the PIC of the present invention. PIC **1100** is nearly identical to HIC **1000** in its function, except that HIC **1000** interfaces the host PCI bus to the XPBus while PIC **1100** interfaces the secondary PCI bus to the XPBus. Similarly, the components in PIC **1100** serve the same function as their corresponding components in HIC **1000**. Reference numbers for components in PIC **1100** have been selected such that a component in PIC **1100** and its corresponding component in HIC **1000** have reference numbers that differ by **500** and have the same two least significant digits. Thus for example, the bus controller in PIC **1100** is referenced as bus controller **1110** while the bus controller in HIC **1000** is referenced as bus controller **1010**. As many of the elements in PIC **1100** serve the same functions as those served by their corresponding elements in HIC **1000** and as the functions of the corresponding elements in HIC **1000** have been described in detail above, the function of elements of PIC **1100** having corresponding elements in HIC **1000** will not be further described herein. Reference may be made to the above description of FIG. **10** for an understanding of the functions of the elements of PIC **1100** having corresponding elements in HIC **1000**.

As suggested above, there are also differences between HIC **1000** and PIC **1100**. Some of the differences between HIC **1000** and PIC **1100** include the following. First, receiver **1140** in PIC **1100**, unlike receiver **1040** in HIC **1000**, does not contain a synchronization unit. As mentioned above, the synchronization unit in HIC **1000** synchronizes the PCKR clock to the PCK clock locally generated by PLL **1050**. PIC **1100** does not locally generate a PCK clock and therefore, it does not have a locally generated PCK clock with which to synchronize the PCK clock signal that it receives from HIC **1000**. Another difference between PIC **1100** and HIC **1000** is the fact that PIC **1100** contains a video parallel to serial converter **1189** whereas HIC **1000** contains a video serial to parallel converter **1080**. Video parallel to serial converter **1189** receives 16 bit parallel video capture data and video control signals on the Video Port Data [0:15] and Video Port Control lines, respectively, from the video capture circuit (not shown in FIG. **11**) and converts them to a serial video data stream that is transmitted on the VPD line to the HIC. The video capture circuit may be any type of

20

video capture circuit that outputs a 16 bit parallel video capture data and video control signals. Another difference lies in the fact that PIC **1100**, unlike HIC **1000**, contains a clock doubler **1182** to double the video clock rate of the video clock signal that it receives. The doubled video clock rate is fed into video parallel to serial converter **1182** through buffer **1183** and is sent to serial to parallel converter **1080** through buffer **1184**. Additionally, reset control unit **1135** in PIC **1100** receives a reset signal from the CPU CNTL & GPIO latch/driver unit **1190** and transmits the reset signal on the RESET# line to the HIC **1000** whereas reset control unit **1045** of HIC **1000** receives the reset signal and forwards it to its CPU CNTL & GPIO latch/driver unit **1090** because, in the above embodiment, the reset signal RESET# is unidirectionally sent from the PIC **1100** to the HIC **1000**.

Like HIC **1000**, PIC **1100** handles the PCI bus control signals and control bits from the XPBus representing PCI control signals in the following ways:

1. PIC **1100** buffers clocked control signals from the secondary PCI bus, encodes them and sends the encoded control bits to the XPBus;
2. PIC **1100** manages the signal locally; and
3. PIC **1100** receives control bits from XPBus, translates them into PCI control signals and sends the PCI control signals to the secondary PCI bus.

PIC **1100** also supports a reference arbiter on the secondary PCI Bus to manage the PCI signals REQ# and GNT#.

FIG. **12** is a table showing the symbols, signals, data rate and description of signals on the XPBus, where RTN indicates a ground (GND) reference. In the above tables, P&D stands for plug and display and is a trademark of the Video Electronics Standards Association (VESA) for the Plug and Display standard, DDC2:SCL and DDC2:SDA stand for the VESA display data channel (DDC) standard 2 clock and data signals, respectively, SV stands for super video, V33 is 3.3 volts, and V5 is 5.0 volts. TMDS stands for Transition Minimized Differential Signaling and is a trademark of Silicon Images and refers to their Panel Link technology, which is in turn a trademark for their LVDS technology. TMDS is used herein to refer to the Panel Link technology or technologies compatible therewith.

FIG. **13** is a table showing the information transmitted on the XPBus during two clock cycles of the XPBus in one embodiment of the present invention where 10 data bits are transmitted in each clock cycle of the XPBus. In FIG. **13**, A00 to A31 represent 32 bits of PCI address A[31:0], D00 to D31 represent 32 bits of PCI data D[31:0], BS0 to BS3 represent 4 bits of bus status data indicating the status of the XPBus, CM0# to CM3# represent 4 bits of PCI command information, BE0# to BE3# represent 4 bits of PCI byte enable information, and CN0 to CN9 represent 10 bits of control information sent in each clock cycle. As shown in FIG. **13**, for each of lines PD0 to PD3, the 10 bit data packets contain one BS bit, one CM/BE bit, and eight A/D bits. For the PCN line, the 10 bit data packet contains 10 CN bits. The first clock cycle shown in FIG. **13** comprises an address cycle in which 4 BS bits, 4 CM bits, 32 A bits and 10 CN bits are sent. The second clock cycle comprises a data cycle in which 4 BS bits, 4 BE bits, 32 D bits and 10 CN bits are sent. The bits transmitted on lines PD0 to PD3 represent 32 PCI AD[31:0] signals, 4 PCI C/BE# [3:0] signals, and part of the function of PCI control signals, such as FRAME#, IRDY#, and TRDY#.

In the embodiment shown in FIG. **13**, BS0 to BS3 are sent at the beginning of each clock cycle. The bus status bits indicate the following bus cycle transactions: idle, address



transfer, write data transfer, read data transfer, switch XDBus direction, last data transfer, wait, and other cycles.

Bits representing signals transmitted between the CPU and South Bridge may also be sent on the lines interconnecting the HIC and PIC, such as lines PCN and PCNR. For example, CPU interface signals such as CPU interrupt (INTR), Address 20 Mask (A20M#), Non-Maskable Interrupt (NMI), System Management Interrupt (SMI#), and Stop Clock (STPCLK#), may be translated into bit information and transmitted on the XDBus between the HIC and the PIC.

FIG. 14 is a table showing the information transmitted on the XDBus during four clock cycles of the XDBus in another embodiment of the present invention where 10 data bits are transmitted in each clock cycle of the XDBus. In this embodiment, the XDBus clock rate is twice as large as the PCI clock rate. This allows sending data and address bits every other XDBus cycle. As can be seen in FIG. 14, there are no address or data bits transmitted during the second or fourth XDBus clock cycle. The fact that the XDBus clock rate is higher than the PCI clock rate allows for compatibility of the XDBus with possible future expansions in the performance of PCI bus to higher data transfer and clock rates.

In the embodiment shown in FIG. 14, there are 18 control bits, CN0 to CN17, transmitted in every two XDBus clock cycles. The first bit transmitted on the control line in each XDBus clock cycle indicates whether control bits CN0 to CN8 or control bits CN9 to CN17 will be transmitted in that cycle. A zero sent at the beginning of a cycle on the control line indicates that CN0 to CN8 will be transmitted during that cycle, whereas a one sent at the beginning of a cycle on the control line indicates that CN9 to CN17 will be transmitted during that cycle. These bits also indicate the presence or absence of data and address bits during that cycle. A zero indicates that address or data bits will be transmitted during that cycle whereas a one indicates that no address or data bits will be transmitted during that cycle.

In one embodiment, BS0 and BS1 are used to encode the PCI signals FRAME# and IRDY#, respectively. Additionally, in one embodiment, BS2 and BS3 are used to indicate the clock speed of the computer bus interface and the type of computer bus interface, respectively. For example, BS2 value of zero may indicate that a 33 MHz PCI bus of 32 bits is used whereas a BS2 value of one may indicate that a 66 MHz PCI bus of 32 bits is used. Similarly, a BS3 value of zero may indicate that a PCI bus is used whereas a BS3 value of one may indicate that another computer interface bus, such as an Institute of Electronics & Electrical Engineers (IEEE) 1394 bus, is used.

FIG. 15 is a schematic diagram of lines PCK, PD0 to PD3, and PCN. These lines are unidirectional LVDS lines for transmitting clock signals and bits such as those shown in FIGS. 13 and 14 from the HIC to the PIC. The bits on the PD0 to PD3 and the PCN lines are sent synchronously within every clock cycle of the PCK. Another set of lines, namely PCKR, PDR0 to PDR3, and PCNR, are used to transmit clock signals and bits from the PIC to HIC. The lines used for transmitting information from the PIC to the HIC have the same structure as those shown in FIG. 15, except that they transmit data in a direction opposite to that in which the lines shown in FIG. 15 transmit data. In other words they transmit information from the PIC to the HIC. The bits on the PDR0 to PDR3 and the PCNR lines are sent synchronously within every clock cycle of the PCKR. Some of the examples of control information that may be sent in the reverse direction, i.e., on PCNR line, include a request to switch data bus direction because of a pending operation (such as read data available), a control signal change in the

target requiring communication in the reverse direction, target busy, and transmission error detected.

The XDBus which includes lines PCK, PD0 to PD3, PCN, PCKR, PDR0 to PDR3, and PCNR, has two sets of unidirectional lines transmitting clock signals and bits in opposite directions. The first set of unidirectional lines includes PCK, PD0 to PD3, and PCN. The second set of unidirectional lines includes PCKR, PDR0 to PDR3, and PCNR. Each of these unidirectional set of lines is a point-to-point bus with a fixed transmitter and receiver, or in other words a fixed master and slave bus. For the first set of unidirectional lines, the HIC is a fixed transmitter/master whereas the PIC is a fixed receiver/slave. For the second set of unidirectional lines, the PIC is a fixed transmitter/master whereas the HIC is a fixed receiver/slave. The LVDS lines of XDBus, a cable friendly and remote system I/O bus, transmit fixed length data packets within a clock cycle.

The XDBus lines, PD0 to PD3, PCN, PDR0 to PDR3 and PCNR, and the video data and clock lines, VPD and VPCK, are not limited to being LVDS lines, as they may be other forms of bit based lines. For example, in another embodiment, the XDBus lines may be IEEE 1394 lines.

It is to be noted that although each of the lines PCK, PD0 to PD3, PCN, PCKR, PDR0 to PDR3, PCNR, VPCK, and VPD is referred to as a line, in the singular rather than plural, each such line may contain more than one physical line. For example, in the embodiment shown in FIG. 23, each of lines PCK, PD0 to PD3 and PCN includes two physical lines between each driver and its corresponding receiver. The term line, when not directly preceded by the terms physical or conductive, is herein used interchangeably with a signal or bit channel which may consist of one or more physical lines for transmitting a signal. In the case of non-differential signal lines, generally only one physical line is used to transmit one signal. However, in the case of differential signal lines, a pair of physical lines is used to transmit one signal. For example, a bit line or bit channel in an LVDS or IEEE 1394 interface consists of a pair of physical lines which together transmit a signal.

A bit based line (i.e., a bit line) is a line for transmitting serial bits. Bit based lines typically transmit bit packets and use a serial data packet protocol. Examples of bit lines include an LVDS line, an IEEE 1394 line, and a Universal Serial Bus (USB) line.

FIG. 16 is a table showing the names, types, number of pins dedicated to, and the description of the primary bus PCI signals. The pins represent those between the host PCI bus and the HIC.

In most embodiments, the ACM includes an enclosure such as the one described with the following components, which should not be limiting:

- 1) A CPU with cache memory;
- 2) Core logic device or means;
- 3) Main memory;
- 4) A single primary Hard Disk Drive "HDD" that has a security program;
- 5) Flash memory with system BIOS and programmable user password;
- 6) Operating System, application software, data files on primary HDD;
- 7) An interface device and connectors to peripheral console;
- 8) A software controllable mechanical lock, lock control means, and other accessories.

The ACM connects to a peripheral console with power supply, a display device, an input device, and other elements.

US 7,363,416 B2

23

Some details of these elements with the present security system are described in more detail below.

FIG. 17 is a simplified layout diagram of a security system for a computer system according to an embodiment of the present invention. This diagram is merely an illustration and should not limit the scope of the claims herein. One of ordinary skill in the art would recognize other variations, modifications, and alternatives. The layout diagram illustrates the top-view of the module 1710, where the backside components (e.g., Host Interface Controller) are depicted in dashed lines. The layout diagram has a first portion, which includes a central processing unit ("CPU") module 1700, and a second portion, which includes a hard drive module 1720. A common printed circuit board 1737 houses these modules and the like. Among other features, the ACM includes the central processing unit module 1700 with a cache memory 1705, which is coupled to a north bridge unit 1721, and a host interface controller 1701. The host interface controller includes a lock control 1703. As shown, the CPU module is disposed on a first portion of the attached computer module, and couples to connectors 1717. Here, the CPU module is spatially located near connector 1717.

The CPU module can use a suitable microprocessing unit, microcontroller, digital signal processor, and the like. In a specific embodiment, the CPU module uses, for example, a 400 MHz Pentium II microprocessor module from Intel Corporation and like microprocessors from AMD Corporation, Cyrix Corporation (now National Semiconductor Corporation), and others. In other aspects, the microprocessor can be one such as the Compaq Computer Corporation Alpha Chip, Apple Computer Corporation PowerPC G3 processor, and the like. Further, higher speed processors are contemplated in other embodiments as technology increases in the future.

In the CPU module, host interface controller 1701 is coupled to BIOS/flash memory 1705. Additionally, the host interface controller is coupled to a clock control logic, a configuration signal, and a peripheral bus. The present invention has a host interface controller that has lock control 1703 to provide security features to the present ACM. Furthermore, the present invention uses a flash memory that includes codes to provide password protection or other electronic security methods.

The second portion of the attached computer module has the hard drive module 1720. Among other elements, the hard drive module includes north bridge 1721, graphics accelerator 1723, graphics memory 1725, a power controller 1727, an IDE controller 1729, and other components. Adjacent to and in parallel alignment with the hard drive module is a personal computer interface ("PCI") bus 1731, 1732. A power regulator 1735 is disposed near the PCI bus.

In a specific embodiment, north bridge unit 1721 often couples to a computer memory, to the graphics accelerator 1723, to the IDE controller, and to the host interface controller via the PCI bus. Graphics accelerator 1723 typically couples to a graphics memory 1723, and other elements. IDE controller 1729 generally supports and provides timing signals necessary for the WDE bus. In the present embodiment, the IDE controller is embodied as a 643U2 PCI-to IDE chip from CMD Technology, for example. Other types of buses than IDE are contemplated, for example EIDE, SCSI, 1394, and the like in alternative embodiments of the present invention.

The hard drive module or mass storage unit 1720 typically includes a computer operating system, application software program files, data files, and the like. In a specific embodiment, the computer operating system may be the Win-

24

dows98 operating system from Microsoft Corporation of Redmond Wash. Other operating systems, such as WindowsNT, MacOS8, Unix, and the like are also contemplated in alternative embodiments of the present invention. Further, some typical application software programs can include Office98 by Microsoft Corporation, Corel Perfect Suite by Corel, and others. Hard disk module 1720 includes a hard disk drive. The hard disk drive, however, can also be replaced by removable hard disk drives, read/write CD ROMs, flash memory, floppy disk drives, and the like. A small form factor, for example 2.5", is currently contemplated, however, other form factors, such as PC card, and the like are also contemplated. Mass storage unit 1720 may also support other interfaces than IDE. Among other features, the computer system includes an ACM with security protection. The ACM connects to the console, which has at least the following elements, which should not be limiting.

- 1) Connection to input devices, e.g. keyboard or mouse;
- 2) Connection to display devices, e.g. Monitor;
- 3) Add-on means, e.g. PCI add-on slots;
- 4) Removable storage media subsystem, e.g. Floppy drive, CDROM drive;
- 5) Communication device, e.g. LAN or modem;
- 6) An interface device and connectors to ACM;
- 7) A computer module bay with a notch in the frame for ACM's lock; and
- 8) Power supply and other accessories.

As noted, the computer module bay is an opening in a peripheral console that receives the ACM. The computer module bay provides mechanical support and protection to ACM. The module bay also includes, among other elements, a variety of thermal components for heat dissipation, a frame that provides connector alignment, and a lock engagement, which secures the ACM to the console. The bay also has a printed circuit board to mount and mate the connector from the ACM to the console. The connector provides an interface between the ACM and other accessories.

FIG. 18 is a simplified block diagram 1800 of a security system for a computer module according to an embodiment of the present invention. This diagram is merely an illustration and should not limit the scope of the claims herein. One of ordinary skill in the art would recognize other variations, modifications, and alternatives. The block diagram 1800 has a variety of features such as those noted above, as well as others. In the present diagram, different reference numerals are used to show the operation of the present system.

The block diagram is an attached computer module 1800. The module 1800 has a central processing unit, which communicates to a north bridge 1841, by way of a CPU bus 1827. The north bridge couples to main memory 1823 via memory bus 1829. The main memory can be any suitable high speed memory device or devices such as dynamic random access memory ("DRAM") integrated circuits and others. The DRAM includes at least 32 Meg. or 617 Meg. and greater of memory, but can also be less depending upon the application. Alternatively, the main memory can be coupled directly with the CPU in some embodiments. The north bridge also couples to a graphics subsystem 1815 via bus 1842. The graphics subsystem can include a graphics accelerator, graphics memory, and other devices. Graphics subsystem transmits a video signal to an interface connector, which couples to a display, for example.

The attached computer module also includes a primary hard disk drive that serves as a main memory unit for programs and the like. The hard disk can be any suitable drive that has at least 2 GB and greater. As merely an example, the hard disk is a Marathon 2250 (2.25 GB, 2½

US 7,363,416 B2

25

inch drive) product made by Seagate Corporation of Scotts Valley, but can be others. The hard disk communicates to the north bridge by way of a hard disk drive controller and bus lines **1802** and **1831**. The hard disk drive controller couples to the north bridge by way of the host PCI bus, which connects bus **1837** to the north bridge. The hard disk includes computer codes that implement a security program according to the present invention. Details of the security program are provided below.

The attached computer module also has a flash memory device **1805** with a BIOS. The flash memory device **1805** also has codes for a user password that can be stored in the device. The flash memory device generally permits the storage of such password without a substantial use of power, even when disconnected. As merely an example, the flash memory device has at least 4 Meg. or greater of memory, or 16 Meg. or greater of memory. A host interface controller **1807** communicates to the north bridge via bus **1835** and host PCI bus. The host interface controller also has a lock control **1809**, which couples to a lock. The lock is attached to the module and has a manual override to the lock on the host interface controller in some embodiments. Host interface controller **1807** communicates to the console using bus **1811**, which couples to connection **1813**.

In a preferred embodiment, the present invention uses a password protection scheme to electronically prevent unauthorized access to the computer module. The present password protection scheme uses a combination of software, which is a portion of the security program, and a user password, which can be stored in the flash memory device **1805**. By way of the flash memory device, the password does not become erased by way of power failure or the lock. The password is substantially fixed in code, which cannot be easily erased. Should the user desire to change the password, it can readily be changed by erasing the code, which is stored in flash memory and a new code (i.e., password) is written into the flash memory. An example of a flash memory device can include a Intel Flash 28F800F3 series flash, which is available in 8 Mbit and 16 Mbit designs. Other types of flash devices can also be used, however. Details of a password protection method are further explained below by way of the FIGS.

In a specific embodiment, the present invention also includes a real-time clock **1810** in the ACM, but is not limited. The real-time clock can be implemented using a reference oscillator 14.31818 MHz **1808** that couples to a real-time clock circuit. The real-time clock circuit can be in the host interface controller. An energy source **1806** such as a battery can be used to keep the real-time clock circuit running even when the ACM has been removed from the console. The real-time clock can be used by a security program to perform a variety of functions. As merely an example, these functions include: (1) fixed time period in which the ACM can be used, e.g., ACM cannot be used at night; (2) programmed ACM to be used after certain date, e.g., high security procedure during owner's vacation or non use period; (3) other uses similar to a programmable time lock. Further details of the present real-time clock are described in the application listed under Ser. No. 09/183,816 noted above.

In still a further embodiment, the present invention also includes a permanent password or user identification code to identify the computer module. In one embodiment, the permanent password or user code is stored in a flash memory device. Alternatively, the permanent password or user code is stored in the central processing unit. The password or user code can be placed in the device upon manufacture of such

26

device. Alternatively, the password or user code can be placed in the device by a one time programming techniques using, for example, fuses or the like. The present password or user code provides a permanent "finger print" on the device, which is generally hardware. The permanent finger print can be used for identification purposes for allowing the user of the hardware to access the hardware itself, as well as other systems. These other systems include local and wide area networks. Alternatively, the systems can also include one or more servers. The present password and user identification can be quite important for electronic commerce applications and the like. In one or more embodiments, the permanent password or user code can be combined with the password on flash memory for the security program, which is described below in more detail.

In one aspect of the invention, the user password is programmable. The password can be programmable by way of the security program. The password can be stored in a flash memory device within the ACM. Accordingly, the user of the ACM and the console would need to have the user password in order to access the ACM. In the present aspect, the combination of a security program and user password can provide the user a wide variety of security functions as follows:

- 1) Auto-lock capability when ACM is inserted into CMB;
- 2) Access privilege of program and data;
- 3) Password matching for ACM removal; and
- 4) Automatic HDD lock out if tempering is detected.

In still a further embodiment, the present invention also includes a method for reading a permanent password or user identification code to identify the computer module. In one embodiment, the permanent password or user code is stored in a flash memory device. Alternatively, the permanent password or user code is stored in the central processing unit. The password or user code can be placed in the device upon manufacture of such device. Alternatively, the password or user code can be placed in the device by a one time programming techniques using, for example, fuses or the like. The present password or user code provides a permanent "finger print" on the device, which is generally hardware. The permanent finger print can be used for identification purposes for allowing the user of the hardware to access the hardware itself, as well as other systems. These other systems include local and wide area networks. Alternatively, the systems can also include one or more servers. The present method allows a third party confirm the user by way of the permanent password or user code. The present password and user identification can be quite important for electronic commerce applications and the like, which verify the user code or password. In one or more embodiments, the permanent password or user code can be combined with the password on flash memory for the security program.

While the above is a full description of the specific embodiments, various modifications, alternative constructions and equivalents may be used. Therefore, the above description and illustrations should not be taken as limiting the scope of the present invention which is defined by the appended claims.

What is claimed is:

1. A computer system comprising:
  - a console comprising a power supply, a first coupling site and a second coupling site, each coupling site comprising a connector and a slot, the console being an enclosure housing
  - the coupling sites,
  - a serial communication hub controller powered by the power supply, and



US 7,363,416 B2

27

a plurality of computer modules; each computer module coupled to one of the coupling site through the connector and the slot, comprising

a processing unit,

a flash memory device configured to store a password for controlling access to the computer module,

a main memory coupled to the processing unit, and

wherein each of the computer modules is substantially similar in design to each other and operates fully independent of each other; and wherein each computer module communicates with the console through two sets of unidirectional serial, differential signal channels which transmit data in opposite directions.

2. The computer system of claim 1 wherein each computer module further comprises a communication controller coupled to the serial communication controller in the console adapted to transfer data between any two of the computer modules and to an external network.

3. The computer system of claim 1 further comprises a hard disk drive coupled to the computer module.

4. The computer system of claim 1 wherein the computer module further comprises an interface controller coupled to a differential signal channel for communicating an encoded serial bit stream of Peripheral Component Interconnect (PCI) bus transaction.

5. The computer system of claim 4 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

6. A computer system comprising:

a console comprising a power supply, a first coupling site and a second coupling site, each coupling site comprising a connector and a slot, the console being an enclosure housing

the coupling sites,

an Ethernet hub controller coupled to an external network and powered by the power supply, and

a plurality of computer modules; each computer module coupled to one of the coupling site through the connector and the slot, comprising

a processing unit,

a flash memory device configured to store a password for controlling access to the computer module,

a main memory coupled to the processing unit,

an interface controller coupled to a differential signal channel for communicating an encoded serial data stream of Peripheral Component Interconnect (PCI) bus transaction, and

a network controller coupled to the Ethernet hub controller through the connector of the coupling site,

wherein each of the computer modules is substantially similar in design to each other.

7. The computer system of claim 6 wherein the differential signal channel comprises two sets of unidirectional serial bit channels which transmit data in opposite directions.

8. The computer system of claim 6 wherein the encoded serial bit stream comprises 10 bit packets.

9. The computer system of claim 6 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

10. The computer system of claim 6 wherein the Ethernet hub controller adapted to transfer data between any two of the computer modules and to the external network.

11. A computer system comprising:

a console comprising a power supply, a first coupling site and a second coupling site, each coupling site comprising a connector and a slot, the console being a first enclosure housing

28

an Ethernet hub controller powered by the power supply, each coupling site, and

a plurality of computer modules, each coupled to one of the coupling sites through the connector and the slot; each computer module comprising

a processing unit,

a main memory coupled to the processing unit,

a mass storage device storing a security program that provides password protection for the computer module,

an interface controller coupled to a differential signal channel for communicating an encoded serial data stream of Peripheral Component Interconnect (PCI) bus transaction, and

an Ethernet controller coupled to the Ethernet hub controller through the connector of the coupling site;

and wherein each of the computer modules operates fully independent of each other.

12. The computer system of claim 11 wherein the differential signal channel comprises two sets of unidirectional serial channels which transmit data in opposite directions.

13. The computer system of claim 11 wherein the Ethernet controllers of the computer modules are used for sharing peripheral devices residing in the console.

14. The computer system of claim 12 wherein each of the unidirectional serial channels comprises one or more pairs of differential signal lines.

15. The computer system of claim 11 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

16. A computer system comprising:

a console comprising a power supply, a first coupling site and a second coupling site, each coupling site comprising a connector and a slot, the console being a first enclosure housing

the coupling sites,

a serial communication hub controller powered by the power supply, and

a plurality of computer modules; each computer module coupled to one of the coupling site through the connector and the slot, comprising

a processing unit,

a main memory coupled to the processing unit,

a mass storage device storing a security program that provides password protection for the computer module,

a communication controller coupled to the serial communication hub controller through the connector of the coupling site, and

an interface controller coupled to a differential signal channel for communicating encoded serial data stream of Peripheral Component Interconnect (PCI) bus transaction;

wherein each of the computer modules operates fully independent of each other.

17. The computer system of claim 16 wherein the encoded serial bit stream comprises 10 bit packets.

18. The computer system of claim 16 wherein the interface controller couples to a flash memory with PCI configuration information.

19. The computer system of claim 16 wherein the computer module further comprises a second enclosure and a hard disk drive wherein the second enclosure houses the hard disk drive.

20. The computer system of claim 16 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

US 7,363,416 B2

29

21. A computer system comprising:  
 a console comprising a video switch, a first coupling site  
 and a second coupling site, each coupling site com-  
 prising a connector and a slot; the console being an  
 enclosure housing  
 the video switch,  
 an Ethernet hub controller coupled to an external network,  
 and  
 a plurality of computer modules; each computer module  
 coupled to one of the coupling sites through the con-  
 nector and the slot, and comprising  
 a processing unit,  
 a main memory coupled to the processing unit,  
 a mass storage device storing a security program that  
 provides password protection for the computer module,  
 a graphics controller coupled to the video switch, and  
 an interface controller coupled to a differential signal  
 channel of two unidirectional serial bit streams which  
 transmit data in opposite directions for communicating  
 encoded serialized Peripheral Component Interconnect  
 (PCI) bus transaction data;  
 wherein each of the computer modules operates fully  
 independent of each other.

22. The computer system of claim 21 wherein the inter-  
 face controller couples to a flash memory with PCI configu-  
 ration information.

23. The computer system of claim 21 wherein the serial  
 bit stream comprises one or more pairs of differential signal  
 lines.

24. The computer system of claim 21 wherein the serial  
 bit stream comprises 10 bit packets.

25. The computer system of claim 21 wherein the serial  
 bit stream comprises PCI bus transaction with encoded PCI  
 address and data bits.

26. A computer system comprising:  
 a console comprising an Ethernet hub controller, a first  
 coupling site and a second coupling site, each coupling  
 site comprising a connector and a slot, the console  
 being an enclosure housing  
 the Ethernet hub controller,  
 each coupling site, and  
 a plurality of computer modules, each coupled to one of  
 the coupling sites through the connector and the slot;  
 each computer module comprising  
 a processing unit,  
 a main memory coupled to the processing unit,  
 a mass storage device storing a security program that  
 provides password protection for the computer module,  
 an interface controller coupled to a differential signal  
 channel for communicating encoded serial bit stream of  
 Peripheral Component Interconnect (PCI) bus transac-  
 tion, and  
 an Ethernet controller coupled to the Ethernet hub con-  
 troller through the connector of the coupling site for  
 communication between the computer modules;  
 wherein each of the computer modules operates indepen-  
 dent of each other, and wherein one of the computer  
 modules can replace another one of the computer  
 modules in operation.

27. The computer system of claim 26 wherein the inter-  
 face controller couples to a flash memory with PCI configu-  
 ration information.

28. The computer system of claim 26 wherein the Ether-  
 net controllers of the computer modules are used for sharing  
 peripheral devices residing in the console.

30

29. The computer system of claim 26 wherein the differ-  
 ential signal channel comprises two sets of unidirectional  
 serial bit channels which transmit data in opposite direc-  
 tions.

30. The computer system of claim 26 wherein the serial  
 bit stream of PCI bus transaction comprises encoded PCI  
 address and data bits.

31. A computer system comprising:  
 a console comprising a first coupling site, and a second  
 coupling site, each coupling site comprising a connec-  
 tor and a slot; the console being an enclosure housing  
 each coupling site, and  
 a plurality of computer modules; each computer module  
 coupled to the coupling site through the connector and  
 the slot, and comprising  
 a processing unit,  
 a main memory coupled to the processing unit,  
 a mass storage device storing a security program that  
 provides password protection for the computer module,  
 an interface controller coupled to a differential signal  
 channel for communicating an encoded serial bit  
 stream of Peripheral Component Interconnect (PCI)  
 bus transaction, and  
 a SCSI hard disk drive;  
 wherein each of the computer modules is substantially  
 similar in design to each other, and wherein one of the  
 computer modules can provide protection against fail-  
 ure of another one of the computer modules.

32. The computer system of claim 31 wherein the encoded  
 serial bit stream comprises 10 bit packets.

33. The computer system of claim 31 wherein the SCSI  
 hard disk drive is removable while the computer module is  
 in operation.

34. The computer system of claim 31 wherein the inter-  
 face controller couples to a flash memory with PCI configu-  
 ration information.

35. The computer system of claim 31 wherein the serial  
 bit stream of PCI bus transaction comprises encoded PCI  
 address and data bits.

36. A computer system comprising:  
 a console comprising an Ethernet controller coupled to an  
 external network, a keyboard/mouse multi-port switch,  
 a first coupling site and a second coupling site, each  
 coupling site comprising a connector and a slot, the  
 console being an enclosure housing the Ethernet con-  
 troller, each coupling site, and  
 a plurality of computer modules, each coupled to one of  
 the coupling sites through the connector and the slot;  
 each computer module comprising  
 a processing unit,  
 a main memory coupled to the processing unit,  
 an interface controller coupled to a differential signal  
 channel for communicating encoded serial bit stream of  
 Peripheral Component Interconnect (PCI) bus transac-  
 tion, and  
 a mass storage device storing a security program that  
 provides password protection for the computer module;  
 wherein each of the computer modules operates fully  
 independent of each other; and wherein the keyboard/  
 mouse multi-port switch switches between keyboard/  
 mouse connection of the computer modules based on a  
 command from a user.

37. The computer system of claim 36 wherein the differ-  
 ential signal channel comprises two sets of unidirectional  
 serial bit channels which transmit data in opposite direc-  
 tions.

US 7,363,416 B2

31

38. The computer system of claim 36 wherein the interface controller couples to a flash memory with PCI configuration information.

39. The computer system of claim 36 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

40. The computer system of claim 36 wherein the command from the user is in the form of either a key on the keyboard or an icon on the screen that the mouse can click on.

41. A computer system comprising:

a console comprising a first coupling site, a second coupling site, each coupling site comprising a connector, the console being an enclosure that is capable of housing

each coupling site,

a serial communication hub controller coupled to an external network, and

a plurality of computer modules inserted into said console; each computer module coupled to one of the connectors of the console and comprising,

a processing unit,

a flash memory device configured to store a password for controlling access to the computer module,

a communication controller coupled to the serial communication hub controller,

a main memory coupled to the processing unit,

an interface controller coupled to a differential signal channel for communicating encoded serial bit stream of Peripheral Component Interconnect (PCI) bus transaction, and

wherein each of the computer modules provide independent processing in the computer system; and wherein one of the computer modules is configured to provide protection against failure of another of the plurality of computer modules.

42. The computer system of claim 41 wherein the differential signal channel comprises two sets of unidirectional serial bit channels which transmit data in opposite directions.

43. The computer system of claim 41 wherein the interface controller couples to a flash memory with PCI configuration information.

44. The computer system of claim 41 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

45. The computer system of claim 41 further comprises a hard disk coupled to the computer module.

46. A computer system comprising:

a console comprising a power supply, a first coupling site, and a second coupling site, each coupling site comprising a connector and a slot, the console being an enclosure housing

each coupling site,

a plurality of computer modules, each coupled to one of the coupling sites through the connector and the slot; each computer module comprising

a processing unit,

a flash memory device configured to store a password for controlling access to the computer module,

a main memory coupled to the processing unit,

a graphics controller, and

an interface controller coupled to a differential signal channel for communicating encoded serialized bit stream of Peripheral Component Interconnect (PCI) bus transaction;

32

wherein each of the computer modules operates fully independent of each other; and wherein the differential signal channel comprises two sets of unidirectional serial channels which transmit data in opposite directions, and wherein one of the computer modules can replace another one of the computer modules in operation.

47. The computer system of claim 46 wherein the encoded serial bit stream comprises 10 bit packets.

48. The computer system of claim 46 wherein each of the unidirectional serial channels comprises one or more pairs of differential signal lines.

49. The computer system of claim 46 wherein the console further houses a power supply that supplies DC power to the Ethernet controller and the computer modules.

50. The computer system of claim 46 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

51. A computer system comprising:

a console comprising an Ethernet hub controller, a first coupling site and a second coupling site, each coupling site comprising a connector and a slot, the console being an enclosure housing the Ethernet hub controller and the coupling sites; and

more than two computer modules, each coupled to one of the coupling site through the connector and the slot, comprising

a processing unit,

a main memory coupled to the processing unit,

an Ethernet controller coupled to the Ethernet hub controller through the connector of the coupling site for communication between the computer modules, and

an interface controller coupled to a differential signal channel for communicating encoded serialized Peripheral Component Interconnect (PCI) bus transaction data;

wherein each of the computer modules operates fully independent of each other; and wherein the differential signal channel comprises two sets of unidirectional serial channels which transmit data in opposite directions; and wherein one of the computer modules is configured to provide protection against failure of any one of the other computer modules.

52. The computer system of claim 51 wherein the Ethernet controllers of the computer modules are used for sharing peripheral devices residing in the console.

53. The computer system of claim 51 wherein the encoded serial bit stream comprises 10 bit packets.

54. The computer system of claim 51 wherein each of the unidirectional serial channels comprises one or more pairs of differential signal lines.

55. The computer system of claim 51 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

56. A computer system comprising:

a console comprising an Ethernet hub controller, a first coupling site and a second coupling site, the console being an enclosure housing

the Ethernet hub controller,

the coupling sites, and

a plurality of computer modules, each coupled to one of the coupling sites; each computer module comprising

a processing unit,

a main memory coupled to the processing unit,

an interface controller coupled to a differential signal channel of two unidirectional serial bit streams which transmit data in opposite directions for communicating



## US 7,363,416 B2

33

encoded serialized Peripheral Component Interconnect (PCI) bus transaction data to a connector, and an Ethernet controller coupled to the Ethernet hub controller for communication between the computer modules;

wherein each of the computer modules operates fully independent of each other.

57. The computer system of claim 56 wherein the differential signal channel comprises two sets of unidirectional serial bit channels which transmit data in opposite directions.

58. The computer system of claim 11 wherein the Ethernet controllers of the computer modules are used for sharing peripheral devices residing in the console.

59. The computer system of claim 56 wherein the encoded serial bit stream comprises 10 bit packets.

60. The computer system of claim 56 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

61. A computer system comprising:

a console comprising an Ethernet controller coupled to an external network, a video switch, a first coupling site and a second coupling site, the console being an enclosure housing the Ethernet controller,

the video switch, each coupling site, and

a plurality of computer modules, each coupled to one of the coupling sites; each computer module comprising a processing unit,

a main memory coupled to the processing unit,

a graphics controller coupled to the video switch, and an interface controller coupled to a differential signal channel of two unidirectional serial bit streams which transmit data in opposite directions for communicating encoded serial Peripheral Component Interconnect (PCI) bus transaction data to a connector;

wherein each of the computer modules operates fully independent of each other.

62. The computer system of claim 61 wherein the interface controller couples to a flash memory with PCI configuration information.

63. The computer system of claim 61 further comprises a hard disk drive coupled to the computer module.

64. The computer system of claim 61 wherein the console further houses a power supply that supplies DC power to the Ethernet controller and the computer modules.

65. The computer system of claim 61 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

66. A computer system comprising:

a console comprising a first coupling site and a second coupling site, the console being an enclosure housing a serial communication hub controller, each coupling site, and

a plurality of computer modules, each coupled to one of the coupling sites; each computer module comprising a processing unit,

a main memory coupled to the processing unit,

a mass storage device storing a security program that provide password protection for the computer module, an interface controller coupled to a differential signal channel of two unidirectional serial bit streams which transmit data in opposite directions for communicating encoded serial Peripheral Component Interconnect (PCI) bus transaction data to a connector, and

34

a communication controller coupled to the serial communication hub controller through the connector of the coupling site for communication between the computer modules;

wherein each of the computer modules operates independent of each other.

67. The computer system of claim 66 wherein the interface controller couples to a flash memory with PCI configuration information.

68. The computer system of claim 66 wherein the hard disk drive is removable while the computer module is in operation.

69. The computer system of claim 66 wherein the encoded serial bit stream comprises 10 bit packets.

70. The computer system of claim 66 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

71. A computer system comprising:

a console comprising a first coupling site, and a second coupling site; the console being an enclosure housing each coupling site,

a serial communication hub controller coupled to an external network, and

a plurality of computer modules, each coupled to one of the coupling sites; each computer module comprising a processing unit,

a main memory coupled to the processing unit,

a flash memory device configured to store a password for controlling access to the computer module,

a communication controller coupled to the serial communication controller to support communication with the external network, and

an interface controller coupled to a differential signal channel of two unidirectional serial bit streams which transmit data in opposite directions for communicating encoded serial Peripheral Component Interconnect (PCI) bus transaction data to a connector;

wherein each of the computer modules operates fully independent of each other; and wherein one of the computer modules can replace another one of the computer modules in operation.

72. The computer system of claim 71 wherein the interface controller couples to a flash memory with PCI configuration information.

73. The computer system of claim 71 further comprises a hard disk drive coupled to the computer module.

74. The computer system of claim 71 wherein the serial bit stream comprises 10 bit packets.

75. The computer system of claim 71 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

76. A computer system comprising:

a console comprising a first coupling site and a second coupling site, each coupling site comprising a connector and a slot, the console being a first enclosure housing each coupling site, and

a plurality of computer modules, each coupled to one of the coupling sites through the connector and the slot; each computer module comprising

a processing unit,

a main memory coupled to the processing unit,

a flash memory device configured to store a password for controlling access to the computer module,

an interface controller coupled to a differential signal channel for communicating an encoded serial bit stream of Peripheral Component Interconnect (PCI) bus transaction, and

US 7,363,416 B2

35

wherein each of the computer modules operates fully independent of each other; and wherein the differential signal channel comprises two sets of unidirectional serial channels which transmit 10 bit packets in opposite directions.

77. The computer system of claim 76 wherein the interface controller couples to a flash memory with PCI configuration information.

78. The computer system of claim 76 wherein each of the unidirectional serial channels comprises one or more pairs of differential signal lines.

79. The computer system of claim 76 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

80. The computer system of claim 76 wherein the console further houses a power supply that supplies DC power to the Ethernet controller and the computer modules.

81. A computer system comprising:

a console comprising an Ethernet controller coupled to an external network, a first coupling site and a second coupling site, each coupling site comprising a connector and a slot, the console being an enclosure housing the Ethernet controller, each coupling site, and

a plurality of computer modules, each coupled to one of the coupling sites through the connector and the slot; each computer module comprising

a processing unit,

a main memory coupled to the processing unit,

a flash memory device configured to store a password for controlling access to the computer module,

a SCSI hard disk drive, and

an interface controller coupled to a differential signal channel for communicating encoded serial bit stream of Peripheral Component Interconnect (PCI) bus transaction;

wherein each of the computer modules operates independent of each other; and wherein the differential signal channel couples to the console through the connector of the coupling site; and wherein the encoded serial bit stream transmits 10 bit packets.

82. The computer system of claim 81 wherein the interface controller couples to a flash memory with PCI configuration information.

83. The computer system of claim 81 wherein the SCSI hard disk drive is removable while the computer module is in operation.

84. The computer system of claim 81 wherein the console further houses a power supply that supplies DC power to the Ethernet controller and the computer modules.

85. The computer system of claim 81 wherein the serial bit stream of PCI bus transaction comprises encoded PCI address and data bits.

86. A computer system comprising:

a console comprising a first coupling site and a second coupling site, each coupling site comprising a connector and a slot, the console being an enclosure housing each coupling site,

a serial communication controller, and

a plurality of computer modules; each computer module coupled to one of the coupling sites through the connector and the slot; each computer module comprising a processing unit,

a main memory coupled to the processing unit,

a flash memory device configured to store a password for controlling access to the computer module,

an interface controller coupled to a differential signal channel of two unidirectional serial bit streams which

36

transmit data in opposite directions for communicating encoded serial, 10 bit packet data stream of Peripheral Component Interconnect (PCI) bus transaction;

wherein each of the computer modules operates independent of each other.

87. The computer system of claim 86 further comprises a hard disk drive coupled to the computer module.

88. The computer system of claim 86 wherein the encoded PCI bus transaction comprises encoded PCI address and data bits.

89. A computer system comprising:

a console comprising a first coupling site and a second coupling site, each coupling site comprising a connector and a slot, the console being an enclosure housing each coupling site, and

a plurality of computer modules; each computer module coupled to one of the coupling sites through the connector and the slot; each computer module comprising

a processing unit,

a main memory coupled to the processing unit,

a flash memory device configured to store a password for controlling access to the computer module,

a mass storage device coupled to the processing unit,

an interface controller coupled to a differential signal channel of two unidirectional serial bit streams which transmit data in opposite directions for communicating encoded serial, 10 bit packet data stream of Peripheral Component Interconnect (PCI) bus transaction; and

wherein each of the computer modules operates independent of each other; and wherein one of the computer modules can replace another one of the computer modules in operation.

90. The computer system of claim 89 wherein the encoded PCI bus transaction comprises encoded PCI address and data bits.

91. The computer system of claim 89 wherein each of the unidirectional serial differential signal channels comprises one or more pairs of differential signal lines.

92. A computer system comprising:

a console comprising a first coupling site and a second coupling site, the console being an enclosure housing each coupling site, and

more than two computer modules; each computer module coupled to one of the coupling sites; each computer module comprising

a processing unit,

a main memory coupled to the processing unit,

a flash memory device configured to store a password for controlling access to the computer module,

a mass storage device coupled to the processing unit,

an interface controller coupled to a differential signal channel of two unidirectional serial bit streams which transmit data in opposite directions for communicating encoded serial bit stream of Peripheral Component Interconnect (PCI) bus transaction to a connector; and

wherein each of the computer modules operates independent of each other; and wherein one of the computer modules is configured to provide protection against failure of any one of the other computer modules.

93. The computer system of claim 92 wherein the encoded PCI bus transaction comprises encoded PCI address and data bits.

94. The computer system of claim 92 wherein each of the unidirectional serial differential signal channels comprises one or more pairs of differential signal lines.

\* \* \* \* \*

(12) **INTER PARTES REEXAMINATION CERTIFICATE (471st)****United States Patent**  
**Chu**(10) **Number:** **US 7,363,416 C1**(45) **Certificate Issued:** **\*Oct. 11, 2012**(54) **COMPUTER SYSTEM UTILIZING MULTIPLE  
COMPUTER MODULES WITH PASSWORD  
PROTECTION**(75) **Inventor:** **William W. Y. Chu**, Los Altos, CA (US)(73) **Assignee:** **ACQIS LLC**, McKinney, TX (US)**Reexamination Request:**

No. 95/001,476, Oct. 27, 2010

**Reexamination Certificate for:**Patent No.: **7,363,416**Issued: **Apr. 22, 2008**Appl. No.: **11/124,851**Filed: **May 4, 2005**(\*) **Notice:** This patent is subject to a terminal disclaimer.**Related U.S. Application Data**


- (63) Continuation of application No. 11/097,694, filed on Mar. 31, 2005, now Pat. No. 7,363,415, which is a continuation of application No. 10/772,214, filed on Feb. 3, 2004, now Pat. No. 7,099,981, which is a continuation of application No. 09/569,758, filed on May 12, 2000, now Pat. No. 6,718,415.
- (60) Provisional application No. 60/134,122, filed on May 14, 1999.

(51) **Int. Cl.**  
**G06F 13/20** (2006.01)(52) **U.S. Cl.** ..... **710/313; 709/227; 710/301; 710/315**(58) **Field of Classification Search** ..... None  
See application file for complete search history.(56) **References Cited**

To view the complete listing of prior art documents cited during the proceeding for Reexamination Control Number 95/001,476, please refer to the USPTO's public Patent Application Information Retrieval (PAIR) system under the Display References tab.

*Primary Examiner* — Majid Banankhah(57) **ABSTRACT**

A computer system for multi-processing purposes. The computer system has a console comprising a first coupling site and a second coupling site. Each coupling site comprises a connector. The console is an enclosure that is capable of housing each coupling site. The system also has a plurality of computer modules, where each of the computer modules is coupled to a connector. Each of the computer modules has a processing unit, a main memory coupled to the processing unit, a graphics controller coupled to the processing unit, and a mass storage device coupled to the processing unit. Each of the computer modules is substantially similar in design to each other to provide independent processing of each of the computer modules in the computer system.



US 7,363,416 C1

**1**  
**INTER PARTES**  
**REEXAMINATION CERTIFICATE**  
**ISSUED UNDER 35 U.S.C. 316**

THE PATENT IS HEREBY AMENDED AS  
INDICATED BELOW.

**2**  
AS A RESULT OF REEXAMINATION, IT HAS BEEN  
DETERMINED THAT:  
  
The patentability of claims **4-94** is confirmed.  
5      Claims **1-3** are cancelled.

\* \* \* \* \*